

Slim Line Series -

SL-2.1R

formerly SF-204F

DESCRIPTION

The **SL-2.1R** is a slim 2-way loudspeaker designed to be surface-mounted and disappear into the architectural surroundings. Its precision ribbon HF driver and two 4" long-excursion LF drivers resolve complex audio program with detail and clarity that does not seem possible from such a small package.

The addition of an available SBC-110 ceiling mounted subwoofer extends low frequency response to 34 Hz and increases maximum system SPL.

KEY FEATURES:

- slim profile (only 2" deep by 4" wide)
- 120° H x 90° V coverage
- employs precision ribbon HF driver
- blends into architectural environment
- easily integrated into architectural casework with optional millwork adapter kit

 $120 - 20,000 \text{ Hz } \pm 3 \text{ dB}$

@ 1 meter

7 lbs.

APPLICATIONS:

Frequency Response

sound for video presentation

NOMINAL DATA

- home theater LCR
- home theater surrounds
- choir-rail foldback / fill

DESCRIPTIVE DATA

(cross-section)

System Configuration

Low profile 2-way

Components & Loading
(2) 4 " long-excursion LF drivers,
(1) 3 " ribbon HF driver

High-Pass Filter

Built-in 1st order @ 120 Hz

Sensitivity 92 dB @ 2.83 volts / 1M Enclosure Type Sealed enclosure, very low profile Impedance 6Ω Steel charges

Impedance 602 Enclosure Material Steel chassis,

Power Handling 90 W long term program with composite endcaps

Maximum Output 108 dB long term / 114 dB peak Finish Black or White

Nominal Coverage Angles 120° H x 90° V Connectors Dual binding head screws

Dimensions height: 18.00 " Suspension Hardware Mounting brackets included width: 4.56 " Grille Integral fabric wrapped

width: 4.56 " Grille Integral, fabric wrapped depth: 2.06 "

West Coast Office

1155-C Arnold Drive, #231 Martinez CA 94553 ph: **925 372-8156** email: orders@innovoxaudio.com

Shipping Weight

Central Office

296 North Pascal Street Saint Paul MN 55104 ph: **612 379-0100**

email: sales@innovoxaudio.com

innovoxaudio.com

(custom colors available)