



Slim Line Series – SL-4.1R

DESCRIPTION

The **SL-4.1R** is an slim 2-way loudspeaker designed to be surface-mounted and disappear into the architectural surroundings. Its precision ribbon HF driver and four 4" long-excursion LF drivers renders complex audio program with detail and clarity that does not seem possible from such a small package.


The addition of an available SBC-210 ceiling mounted sub-woofer extends low frequency response to 34 Hz and increases maximum system SPL.

KEY FEATURES:

- slim profile (only 2" deep by 4" wide)
- 120° H x 90° V coverage
- employs precision ribbon HF driver
- blends into architectural environment
- easily integrated into architectural casework with optional millwork adapter kit

APPLICATIONS:

- sound for video presentation
- premium home theater LCR
- premium home theater surrounds
- delay fill
- theatrical effects



NOMINAL DATA

Frequency Response	120 – 20,000 Hz ± 3 dB
Sensitivity	92 dB @ 2.83 volts / 1M
Impedance	6Ω
Power Handling	100 W peak
Maximum Output	114 dB peak, @ 1 meter on axis, averaged from 300-3,000 Hz
Nominal Coverage Angles	120° H x 90° V
Dimensions	height: 30.50 " width: 4.56 " depth: 2.06 "
Shipping Weight	15 lbs.

DESCRIPTIVE DATA

System Configuration	Low profile 2-way
Components & Loading	(4) 4 " long-excursion LF drivers; (1) 3" ribbon HF driver
High-Pass Filter	Built-in 1 st order @ 120 Hz
Enclosure Type	Sealed enclosure, very low profile
Enclosure Material	Steel chassis, with composite endcaps
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	Mounting brackets included
Grille	Integral, fabric wrapped

West Coast Office
1155-C Arnold Drive, #231
Martinez CA 94553
ph: **925 372-8156**
email: orders@innovoxaudio.com

Central Office
296 North Pascal Street
Saint Paul MN 55104
ph: **612 379-0100**
email: sales@innovoxaudio.com

innovoxaudio.com