

SLA Series -

SLA-6.1

formerly LA-1425

DESCRIPTION

The **SLA-6.1** is a high output Frequency Shaded Line Array loudspeaker employing a ribbon HF driver and six 4" LF drivers within a very low profile enclosure. It is designed to work in highly reverberant environments where very broad, uniform horizontal coverage and a focused vertical pattern are beneficial.

A sophisticated filter circuit sequentially integrates drivers in the array to maintain pattern control to 600 Hz, and ensures a smooth transition from line-source to point-source behavior at lower frequencies. The result is very flat response and uniform pattern control, yielding superior speech clarity and musical detail.

KEY FEATURES:

- maintains 25° vertical pattern control to 600 Hz
- low profile: depth only 3.4"
- Frequency Shading optimizes pattern uniformity
- effective projection beyond 75 feet

APPLICATIONS:

- churches
- lecture halls
- transit centers
- presentation spaces
- performing arts centers





DESCRIPTIVE DATA

NOMINAL DATA

 $\begin{tabular}{lll} Frequency Response & 120-20,000 \ Hz, \pm 3 \ dB \\ Sensitivity & 95 \ dB @ 2.83V \ / \ 1M \\ Impedance & 8\Omega \ (70-volt available) \\ Power Handling & 200 \ W \ long \ term \ (AES-2) \\ Maximum Output & 116 \ dB \ long-term, 122 \ dB \ peak \\ \end{tabular}$

Nominal Coverage Angles 120° H x 25° V

Dimensions height: 34.50 " / 876 mm width: 5.62 " / 143 mm depth: 3.38 " / 86 mm

Net Weight 15.6 lbs / 7.6 kg Shipping Weight 18.6 lbs / 8.5 kg System Configuration Compact frequency-shaded line array

Components & Loading (6) 4" LF; (1) ribbon HF

Connectors

Suspension Hardware

Recommended High-Pass 4th order Butterworth @ 100 Hz

Enclosure Type Sealed enclosure, low profile column

Enclosure Material Steel, composite endcaps

Finish Black or White standard

(custom colors available)

NL4 and dual binding head screws

(10) ¼-20 threaded points on back and endcaps – OmniMount 30.0 series compatible (two slotted L-brackets

compatible (two slotted Lincluded)

Grille Integral, fabric wrapped

West Coast Office

1155-C Arnold Drive, #231 Martinez CA 94553 ph: **925 372-8156** email: orders@innovoxaudio.com

Central Office

296 North Pascal Street Saint Paul MN 55104 ph: **612 379-0100**

email: sales@innovoxaudio.com

innovoxaudio.com