



CVC-675 COLOR CCD IN-WALL CAMERA

INTRODUCTION

THIS CCD COLOR 18 GAUGE STAINLESS STEEL IN-WALL CAMERA FEATURES AN EXCEPTIONAL FIELD OF VIEW. FITS INTO A SINGLE GANG ELECTRICAL BOX WITH 350 LINES OF RESOLUTION AND A BUILT-IN ELECTRONIC IRIS, THE CVC-675 OFFERS A SHARP IMAGE IN A VARIETY OF LIGHTING CONDITIONS. THE BNC STYLE VIDEO OUTPUT CAN BE CONNECTED TO THE VIDEO INPUT OF A TV, VCR OR MONITOR. A REGULATED 12V DC POWER SUPPLY IS INCLUDED.

NOTE : POWER SUPPLY MUST BE CENTER POSITIVE.

CABLE OUTPUTS BNC - VIDEO
 DC JACK - POWER

SPECIFICATIONS

IMAGE DEVICE	1/4" INTERLINE COLOR CCD
SCANNING SYSTEM	NTSC COLOR 525 TV LINES 60 FIELDS/Sec.
EFFECTIVE PIXEL ARRAY	512(HORIZONTAL) X 492(VERTICAL)
RESOLUTION	350 TV LINES
SHUTTER CONTROL	AUTO 1/60 ~ 1/100,000 Sec
LENS/ANGLE OF VIEW	3.6mm, 92° F1.6
SCANNING FREQUENCY	HOR. 15.734KHZ, VERT. 60HZ
MINIMUM ILLUMINATION	1 Lux
VIDEO S/N RATIO	GREATER THAN 48dB
VIDEO OUTPUT LEVEL	COLOR COMPOSITE VIDEO SIGNAL 1Vp-p/75Ω
POWER REQUIREMENTS	12V DC SUPPLIED BY AC ADAPTOR - UL & CSA
POWER CONSUMPTION	230mA TYP.
OPERATING TEMPERATURE	14° F ~ 122° F
DIMENSIONS	2.75"L x 2.75"W x 4.25"H
WEIGHT	APPROX. 3.6 Oz (APPROX. 102g)

Speco Technologies

200 NEW HIGHWAY, P.O.BOX 726, AMITYVILLE, NEW YORK 11701-0726
631-957-8700, 1-800-645-5516, FAX 631-957-9142 www.specotech.com

ALWAYS USE DISCRETION WHEN INSTALLING VIDEO AND/OR AUDIO SURVEILLANCE EQUIPMENT ESPECIALLY WHEN THERE IS PERCEIVED PRIVACY, OR AN EXPECTATION OF PRIVACY. INQUIRE REGARDING FEDERAL, STATE AND/OR LOCAL REGULATIONS APPLICABLE TO THE LAWFUL INSTALLATION OF VIDEO AND/OR AUDIO RECORDING OR SURVEILLANCE EQUIPMENT. PARTY CONSENT MAY BE REQUIRED.