

Speco Technologies has upscaled the look of our popular 8" 70 Volt commercial ceiling speaker line. This new design is matched with the same high performance sound quality as our older model; for the same economical price.

Features

- 6" or 8" speaker combination with transformer & mounted grille
- 8 Ohm impedance
- 10W RMS power
- 15W max. power
- 5 oz. magnet
- 5W Dual 70/25V transformer (with taps at 5, 2.5, 1, .5, .25 & 8 Ohms)



Classic



G86TG
G86TCG

8" Dual Paper Cone Ceiling Speaker with Transformer

8" Dual Paper Cone Ceiling Speaker with Transformer & Volume Control

Modern



SPG66T
SPG86T

6" Dual Paper Cone Ceiling Speaker with Transformer

8" Dual Paper Cone Ceiling Speaker with Transformer

Specifications:	G86TG	G86TCG	SPG66T	SPG86T
Frequency Response:	85Hz~20kHz	85Hz~20kHz	120Hz~20kHz	90Hz~20kHz
Sensitivity:	90±3dB 1W/1m	90±3dB 1W/1m	91±3dB 1W/1m	91±3dB 1W/1m
Outer Dimensions:	13" Diameter X 3.5" Depth	13" Diameter X 3.5" Depth	9" X 3" Depth	10.75" X 3.2" Depth
Cutout Dimensions:	11.3"	11.3"	7"	9.5"
Mounting Hardware:	TS8 Ceiling Tile Bracket or STH8 Back Can (Optional - Both Sold Separately)		Built-in easy mount tabs	Built-in easy mount tabs

Speco Technologies is constantly developing product improvements. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 4/5/10

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880

www.specotech.com