

M1280B MINIATURE CONDENSER MICROPHONE

OVERVIEW:

The M1280B, a miniaturized condenser microphone with a fully integrated preamp and detachable cable, has complete immunity from RF interference caused by cell phones and GSM devices. The M1280B, which is equipped with a cardioid capsule, is also available with hypercardioid, omni or shotgun capsules, giving the microphone the unique ability to be used in a wide variety of live, studio and broadcast applications.

The M1280B is available with a wide array of clips and accessories allowing the microphone to be used for drums, percussion, musical instruments, overhead stage miking, podiums, conferences and presentations.

SUPPLIED ACCESSORIES:

25' cable with mini-XLRf - XLRm connectors (CBL-M25)
Mic stand adapter (MC-MICRO)
Hanging clip (MC-HANGER)
External foam windscreen (WS1218)

OPTIONAL ACCESSORIES:

MICROBOOM - 50-inch carbon fiber boom arm with clutch assembly
SMT-MICRO - Stand adapter with rubber insulated shockmount
DCLAMP-MICRO - Lug mount adapted for hand percussion instruments with shockmount ring
DFLEX-MICRO - Wide jaw butterfly clip with shockmount ring
DVICE-MICRO - Drum rim mount attachment with shockmount ring
MC20i - Clamp on clip for saxophone with shockmount ring
MGN-6 - 6-inch gooseneck with base terminating in standard XLRm
MGN-14 - Same as MGN-6 in 14 inch length
MGN-20 - Same as MGN-6 in 20 inch length

MODEL VARIATIONS:

M1280B-HC - Same as M1280B with hypercardioid capsule
M1280B-O - Same as above with omni-directional capsule
M1280B-S - Same as above with supercardioid (shotgun) capsule

with RFI immunity



FEATURES:

Small, lightweight, low profile
Miniaturized integrated preamp circuitry
No external power adapter needed
12 mm gold vapor diaphragm
Immune to RF interference
Extremely low noise, high SPL handling
Available with a cardioid, hypercardioid, omni or shotgun capsule

APPLICATIONS:

Overhead mic for choir, group vocal
Acoustic instruments
Ambient room miking
Symphonic area miking
Speech / Presentation
Cymbals / Percussion




M1280B on DFLEX



MC-MICRO



M1280B on MC-HANGER





MICROBOOM

SPECIFICATIONS:

Transducer Type	Condenser
Frequency Response	40 Hz - 20 kHz
Polar Pattern	Cardioid
	Hypercardioid
	Omni
	Supercardioid
Output Impedance	150 ohms
Sensitivity	10.4 mV / Pa (C) @ 1k
	9.8 mV / Pa (HC) @ 1k
	12 mV / Pa (O) @ 1k
	18.3 mV / Pa (S)
Signal/Noise Ratio (A-weighted)	73 dB
Equivalent Noise Level (A-weighted)	21 dB
Maximum SPL @ .5% THD	≥150 dB
Dynamic Range	129 dB
Power Requirements	48 – 52 V
Connector	3 pin mini-XLRm
Polarity	Positive pressure on diaphragm produces positive voltage on pin 2 relative to pin 3
Housing / Finish	Machined brass / Powder coat
Weight	19 g / .67 ounces
Length	67 mm / 2.6 inches

FREQUENCY / POLARS:



ARCHITECTS AND ENGINEERS SPECIFICATIONS:

The microphone shall be of the condenser type with a modular threaded capsule available in cardioid, hypercardioid, omni-directional and supercardioid polar patterns. The microphone shall be protected from RF interference. The microphone shall have a fully integrated preamp circuitry thereby eliminating the need for a remote preamplifier module. The microphone shall operate on 48 - 52 Volts DC and the nominal output impedance shall be equal to 150 ohms at 1 kHz. The microphone shall have a sensitivity at 1 kHz of 10.4 mV / Pa in cardioid, 9.8 mV / Pa in hypercardioid, 12 mV / Pa in omni and 18.3 mV / Pa in supercardioid. The microphone shall have a maximum SPL level of 150 dB with THD of .5% and the microphone shall be machined out of brass and the dimensions shall be 12 mm in diameter by 67 mm in length. The microphone shall be the Audix M1280B.

OPERATION:

The M1280B is a low impedance microphone and should be plugged into a "mic level" input on your console, mixer or recording device. The M1280B requires phantom power and will NOT operate without phantom power voltage (48 Volts recommended) which is available on most professional mic preamps and mixing devices. If phantom power is not available on your equipment, you will have to procure a phantom power supply (such as the Audix APS2). Avoid plugging or unplugging the microphone from a PA system unless the channel is muted or the volume of the system turned down. Failure to do so may result in a loud "popping" noise which could seriously damage the speakers in the PA system.

USER TIPS:

The M1280B, despite its size, has all the attributes of a world class recording microphone. Low noise integrated electronics allows the microphone to function in the close field as well as in the far field. It can be used on a wide variety of acoustics instruments as well as on voice and vocal ensembles.

Polar patterns: The M1280B is offered in 4 different polar patterns to help you achieve optimum results. **Cardioid (M1280B):** In general, the cardioid pattern is the most widely used as it offers a good balance between the sound of the instrument or voice within the context of the room or venue. The cardioid pattern is also helpful with resistance to feedback. For acoustic instruments, in general, the working range will depend on the sound pressure levels produced by the instrument. For percussion, as an example, the M1280B could be used 1 - 2 feet above the cymbals, or because of its small size, could also be used in hard to reach areas such as beneath the cymbals. For orchestral instruments, the M1280B may be positioned anywhere from 3 - 12 inches depending on instrument and room acoustics. For speech or single voice the typical working distance is 8 - 10 inches. For area miking or group vocals the working distance can be between 2 - 3 feet from the sound source (see ADX40 and MB1250B for choir miking).


Hypercardioid (M1280B-HC): In situations where the volume is loud on stage or there are many open microphones, this pattern is helpful in further isolating the instrument or vocal from the rest of the instruments on stage. The microphone can be worked at 1/2 the distance of cardioid if necessary.

Supercardioid (M1280B-S): This polar pattern, also known as a shotgun pick up pattern, has a longer reach and more narrow pattern than the other cardioid patterns. This pattern is best for podium applications. It is helpful in pin-pointing hard to reach areas, especially for recording outdoors, and with video.

Omni-Directional (M1280B-O): This pattern picks up from all directions, offering very little in the way of isolation or feedback control. However, the Omni pattern offers the most accurate and natural sound reproduction of all the patterns. It is ideal for recording, live broadcasts or video, where sound reinforcement speakers are not an issue.

*Further miking techniques may be found on our website at www.audixusa.com

DIMENSIONS (mm):



***All specifications subject to change without notice.

SERVICE AND WARRANTY:

This microphone is under warranty for a period of 3 years from any and all manufacturing defects. Should your microphone fail in any way, please contact the Audix Service department at 503-682-6933. A Return Authorization number is required before returning any products.

CARE AND MAINTENANCE:

The M1280B is manufactured to exacting specs with roadworthy construction. However, the capsule is highly sensitive and should be handled with care. Avoid extreme temperatures and be sure to store your microphone in the pouch provided when not in use. Moisture of any kind can adversely affect the sound and performance of your microphone.



Audix Corporation 9400 SW Barber St. Wilsonville, OR 97070

www.audixusa.com
503-682-6933 Fax: 503-682-7114



AUDIX WARRANTY REGISTRATION FORM

Name: _____ Model: _____
 Company: _____ Serial Number: _____
 Address: _____ Store: _____
 City: _____ Store Location: _____
 Prov./State: _____ Zip: _____ Purchase Date: _____
 Phone: () _____ Signature: _____
 Email: _____ Date: _____

Please Check all that apply:

Male Female

Age:

- 18 or Under
- 19-25
- 26-35
- 36-45
- 46-55
- 55 +

Occupation:

- Musician
- Producer
- Sound Eng.
- Radio/TV
- Production
- Other _____

Primary Instruments:

- Vocal
- Guitar / Bass
- Drums
- Keyboard
- Brass
- Woodwinds
- Strings
- Other _____

Product to be used for:

- Pro live sound
- Pro recording
- Home recording
- Rehearsal
- Installation
- School
- House of Worship
- Other _____

How did you hear about Audix?

- Magazine Ad
- On-line Store
- Salesman
- Online Ad
- Friend
- Other _____

Do you own other Audix Products? Yes No

Model(s) _____

Have you visited the Audix website? Yes No

Please register your product online at www.audixusa.com or mail this form to:
 Audix Microphones P.O. Box 4010 Wilsonville, OR 97070