

PLL1910M



Specification

Product Name

Planar Part Number

Viewable Size

Aspect Ratio

Contrast Ratio (typ)

Viewing Angle (typ)

Response Time (typ)

Brightness (Typical)

Display Type

Display Resolution

Tilt Range

Palette

Pixel Pitch

Refresh Rate

Dimensions (W x H x D)

Dimensions without Stand

Panel Depth

Display Weight

Shipping weight

Video Inputs

External Connections

Audio Output

Compatibility

Power Supply

Detail

PLL1910M

997-6958-00

19" diagonal (14.81" horizontal x 11.85" vertical)

5:4

1000:1

170° Horizontal and 160° Vertical (Specified at CR>10:1)

5 ms

250 cd/m²

Edge-Lit LED LCD

1280 x 1024 SXGA

0° to +20°

16.7 million colors

0.294 mm

55~76 Hz (60 Hz recommended)

16.0" x 16.0" x 7.0" (407.1 mm x 406.9 mm x 177.8 mm)

16.0" x 13.8" x 2.4" (407.1 mm x 349.3 mm x 60.4 mm)

2.4" (60.4 mm)

6.6 lbs (3 kgs), 6.1 lbs (2.75 kgs) without base & stand

9.6 lbs (4.35 kgs)

Digital (DVI-D w/HDCP), Analog (VGA)

(1) DVI 24-pin connector, (1) Analog VGA D-sub 15-pin video display, (1) 1/8 inch audio input jack

2W x 2

PC and Mac® (adapter may be required for Mac)

Internal

Power Consumption	22W typical (<0.5W standby)
Power Requirements	AC 100/240 VAC
VESA Compatible/Location	Built-in 100 mm VESA, back
Product Approvals	FCC-B, CE, UL/cUL, RoHS
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only)
Options / Features	Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
In the Box	PLL1910M 19" LED LCD Monitor, Power Cord, VGA Cable, DVI Cable, Audio Cable, User's Guide
UPC	8 10689 06958 4

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 5/7/2013

(c)Copyright 2013 Planar Systems, Inc. All rights reserved