

Description:

The LDSR Series rack measures 18" [457mm] deep at base and features a 12-degree slope so equipment can be easily viewed from a seated position. Sturdy design is 16-gauge certified US steel, with fixed front mounting rails tapped 10-32 and recessed 0.562" [14mm] from frame, providing approximately 0.75" [19mm] for equipment clearance. Open back allows easy access to rear equipment controls. This rack will not accept a front door so equipment with protruding knobs or patch panel connections is not a problem. Rack includes rubber feet to protect desktop from scratches or you can order the optional protective runner kit (model PRK) for slide-in applications.

Features:

- Fixed Front Mounting Rails: 1-pr. tapped 10-32
- Protective rubber feet add .5" [13mm] to rack height
- Open base, front and back
- Black wrinkle powder epoxy finish
- Made in the USA
- Suitable for UPS shipping



A&E Specifications:

Rack for desktop use shall be Lowell Model _____. It shall have a 12-degree front slope and measure 21.1"W x 18"D [536mm x 457mm] at base. Height shall be _____ rack units. Welded assembly shall be 16-gauge steel with fixed front mounting rails tapped 10-32. The rack shall include protective rubber feet. Finish shall be black wrinkle powder epoxy.

Options:

- **Rear Rails:** fixed-position rails mount in rear of rack, includes hardware.
- **Rear Access Cover:** steel cover closes back of rack. *Note: cover cannot be used in conjunction with (optional) rear mounting rails.*
- **Protective Runner Kit:** plastic glides protect wood surfaces when rack is installed inside cabinetry.

Model No.	Description	Racking Height	Overall Height	Overall Height (w feet)	Overall Width	Overall Depth
LDSR-718	Desktop rack with sloped front	12.375 in / 314 mm / 7U	14.21 in / 361 mm	14.71 in / 374 mm	21.10 in / 536 mm	18 in / 457 mm
LDSR-1018	Desktop rack with sloped front	17.625 in / 448 mm / 10U	19.35 in / 491 mm	19.85 in / 504 mm	21.10 in / 536 mm	18 in / 457 mm
LDSR-1218	Desktop rack with sloped front	21.125 in / 537 mm / 12U	22.77 in / 578 mm	23.27 in / 591 mm	21.10 in / 536 mm	18 in / 457 mm
RRTF-7	1-pr. rear rack rails with hardware	7U				
RRTF-10	1-pr. rear rack rails with hardware	10U				
RRTF-12	1-pr. rear rack rails with hardware	12U				
LDTR-RAC7	Rear Access Cover *	7U				
LDTR-RAC10	Rear Access Cover *	10U				
LDTR-RAC12	Rear Access Cover *	12U				
PRK	Protective Runner Kit					

One rack unit (RU or U) = 1.75 inches or 44.45 mm. Some measurements have been rounded.
* Rear Access Cover cannot be used in conjunction with optional rear rails.

