



DESCRIPTION

The GAD GT-5301™ is a three-way, bass reflex loudspeaker system featuring flat frequency response, low distortion and wide dynamic range. Design for permanent and semi-permanent applications.

The GT-5301™ is available with optional 3/8" - 16 threaded mounting points which permits safe, load-rated suspension in permanent installations.



APPLICATION

The GT-5301™ is designed for near field / far field applications where a smooth, dynamic range is needed. The GT-5301™ is an ideal choice for either analog or digital reproductions where clean, clear response is a must. The GT-5301™ boasts a wide-range dispersion for portable A/V events or even for side fill or delay monitoring applications.

SPECIFICATIONS DATA

Frequency Response (1 watt @ 1M)	±3 db 40 Hz 19.5 kHz	
Sensitivity (1 watt @ 1M)	(2.83V) 99 db SPL	
Power Handling	AES standard 350 watts	
Nominal Impedance	8 ohm	
Dispersion	Horizontal 90°	
	Vertical 90°	
Cabinet Type	Trapezoidal 15°	
Finish	Black Spatter	
Connectors	2 x Neutrik® NL4 Speakon	
Grille	Powder-Coated, Perforated Steel	
Crossover Frequency	400/2.2k Hz with 18 db per octave slope	
Components	LF: 15" cone MF: 6" cone HF: 1" compression driver	

Dimensions	Inches		Millimeters	
	Height	28.75"		730.3
Width	18.50"		469.9	
Depth	18.50"		469.9	
Weight	Pounds		Kilograms	
	Net Weight	60		27.2

grundorf
corp.™

712-322-3900
FAX 712-322-3407

Visit us online at www.grundaudio.com
Email: sales@grundaudio.com
721 Ninth Avenue - Council Bluffs, IA 51501