

Copyette Technical Specs Chart

<b>COPYETTE EH</b>	<b>1-2-1 Mono</b>	<b>1-2-1 Stereo</b>	<b>1-2-3 Mono</b>	<b>1-2-3 Stereo</b>
Track Configuration	1/2 Track 2 Channel	1/4 Track 4 Channel	1/2 Track 2 Channel	1/2 Track 4 Channel
Copy Speed: (60 Hz)	30 ips (76 cm/s)	30 ips (76 cm/s)	30 ips (76 cm/s)	30 ips (76 cm/s)
Copy Speed: (50 Hz)	25ips (63 cm/s)	25ips (63 cm/s)	30ips (63 cm/s)	30ips (63 cm/s)
Freq. Response	50 Hz-6.3 Hz	50 Hz-8 Hz	50 Hz-8 Hz	50 Hz-8 Hz
Equalization(EIA)	Type 1	Type 1	Type 1	Type 1
Signal-to-noise ratio	48dB	48dB	48dB	48dB
Erase heads	Yes	Yes	Yes	Yes
Crosstalk Rejection, Typically at 1 kHz	50 dB or greater Channel 1-2	50 dB or greater Channel 2-3	50 dB or greater Channel 1-2	50 dB or greater Channel 2-3
Distortion, typically at nominal level	Below 1% T.H.D.	Below 1% T.H.D.	Below 1% T.H.D.	Below 1% T.H.D.
Flutter/Wow (RMS Weighted)	0.35% WRMS	0.35% WRMS	0.35% WRMS	0.35% WRMS
Bias Oscillator	500 kHz	500 kHz	500 kHz	500 kHz
Record Level, Typically at 1 kHz	Within 2 dB of original	Within 2 dB of original	Within 2 dB of original	Within 2 dB of original
Distortion, typically at nominal level	Below 1% T.H.D.	Below 1% T.H.D.	Below 1% T.H.D.	Below 1% T.H.D.
Power Req. 100V	90-110 VAC 50/60 Hz, 70 Watts		90-110 VAC 50/60 Hz, 70 Watts	
Power Req. 120 V	105-125 VAC 60 Hz, 65 Watts		105-125 VAC 60 Hz, 65 Watts	
Power Req. 240 V	235-260 VAC 50 Hz, 75 Watts		235-260 VAC 50 Hz, 75 Watts	
Weight 100-120 V	10 lbs. (4.5 kg)	10 lbs. (4.5 kg)	14 lbs. (6.3 kg)	14 lbs. (6.3 kg)
Weight 220-240V	10 lbs. (4.5 kg)	10 lbs. (4.5 kg)	14 lbs. (6.3 kg)	14 lbs. (6.3 kg)
Head Warranty	90 Days	90 Days	90 Days	90 Days
Unit Warranty	1 Year	1 Year	1 Year	1 Year