

LED-1908HDR - Front



LED-1908HDR

This LED-backlit rack mount monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Analog video is very clear with no detail loss Displays 1080i/p digital video 3D Comb Filter for better picture quality
3D Comb Filter for better picture quality
,
High contrast ratio for better picture definition
Durable metal case

Related Products	
LED-1908HD	
LED-1908HDL	
LED-1908HDVB	
LED-1708HD	
LED-1708HDL	
LED-1708HDR	

Considerations	
Specifications	David and the OPILI
Mount	Rack mount: 9RU
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	n/a
Selectable Color Temp.	Yes
Case	Durable Metal
Built-in Power Supply	No
IR Remote Control	No
180° Rotation Display	No
Native Aspect Ratio	5:4
Visible Screen Size (WH)	376.3 x 301 / 14.8" x 11.8"
Resolution	1280(H) x 1024(V) dots
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1
Back Light	LED
PC Compatibility	Yes
Dot Pitch	0.294(H) x 0.294(V)
Colors	16.7 M
Number of Pixels	1,310,720
ResponseTime	5 ms
Audio Power / Speakers	1.5W x 2
Viewing Angle (L/R/T/B)	170/170/160/160 degrees
Pixel Configuration	Stripe
Input Signal	Analog and Digital audio/video
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Removable Desk Stand	n/a
Dimensions w/ Deskstand	n/a
Dimensions w/o Deskstand	9RU x 2.9"
Operating Temp/Humidity	32 ~ 104°F / 0 ~ 40°C,10% ~ 90% humidity
Power Requirements	DC 12V (AC100~240)[50/60]
Power Consumption	15W Max
Component	No
Composite	BNC IN/OUT x 2
S-Video	No
PC	VGA in/out 15 pin D-sub
HDMI / DVI / RS-232	Yes/No/No
Audio	RCA audio inputs, PC stereo in
Power	2.1mm DC IN jack
Weight	5.65Kgs/12.43 lbs
GSA	Yes