

# The Light Source

## Purlin Clamp



The Purlin Clamp is perfect for installing to purlins, I-beams and bar joists up to 1" thick. 1/2" x 2.5" square head set screw for locking onto I-beam. 1/2" x 1" grade 5 Hex Head Bolt supplied to connect load or use for 1/2" - 13 tpi threaded rod. Micro-grooves for secure connection to beam. 1" thick.

The Purlin Clamp is also available with a 3/8" x 2.5" square head set screw. The # PCM3/8.

<b>Safe Vertical Working Load</b>	500 lbs. for 1/2" and 300 lbs for 3/8"
<b>Hardware</b>	1/2 x 2-1/2" Square Head Set Screw or 3/8 x 2-1/2" Square Head Set Screw .5 x 1" Hex Head Cap Screw 1" Belleville Washer
<b>Dimensions</b>	3 3/8" x 3 7/8"
<b>Weight</b>	0.40 lb.
<b>Case Quantities</b>	each
<b>Order Codes</b>	<b>PCMI/2</b> Purlin Clamp, 1/2" Fasteners, Silver <b>PCM3/8</b> Purlin Clamp, 3/8" Fasteners, Silver <b>PCBI/2</b> Purlin Clamp, 1/2" Fasteners, Black Anodized <b>PCB3/8</b> Purlin Clamp, 3/8" Fasteners, Black Anodized