

PRG-EXA(-S)(-W)
 PRG-EXB(-S)(-W)
 PRG-EXC(-S)(-W)

PRG Series Adjustable Projector Ceiling/Wall Mount Kit

For Multimedia Projectors up to 50 lb (22 kg)

Peerless has packaged flexibility and ease together in one box with these ceiling/wall mounting kits, which enable the installation of a projector from either the ceiling or the wall. This all-in-one kit includes the industry's first precision gear projector mount that delivers precision image alignment with a simple turn of a knob. These comprehensive projector mounting kits also include an adjustable length column that provides ideal height positioning for the perfect projector installation. Concealed within the column is a cable-management channel, assuring a clean and clutter-free appearance.



Max load: 50 lb (22 kg)



FEATURES

- Continuous channel design for uninterrupted drop length or wall extension adjustments
- Three adjustable extension lengths:
 PRG-EXA models: (ceiling/wall) 8.7"-12.8" (221-325 mm)
 9.72" -13.86" (247-352 mm)
 PRG-EXB models: (ceiling/wall) 12.68"-20.67" (322-525 mm)
 13.74" - 21.73" (349-552 mm)
 PRG-EXC models: (ceiling only) 19.13"-32.91" (486-836 mm)
- Safety catch designed into extension to ensure user and equipment safety
- Mounts to ceiling or wall (according to model) with included wall mount interface
- Spider® Universal Adapter Plate extends up to 17.63" (448 mm) to fit most projector models
- Internal cable management within channels for clean, clutter-free appearance
- Includes PRG Precision Gear Projector Mount that provides pin-point image alignment with the unique gearing system by simply adjusting two knobs
- Specifications:
 Tilt: ±20°
 Roll: ±10°
 Swivel: 360°

■ **ACHIEVE IDEAL PLACEMENT**
 Continuous channel design for uninterrupted drop length or wall extension adjustments

■ **PIN-POINT IMAGE ALIGNMENT**
 Includes PRG Precision Gear Projector Mount that provides pin-point image alignment with its unique gearing system by simply adjusting two knobs

■ **ADDED PEACE-OF-MIND**
 Incorporates safety catch design into extension channels to ensure user and equipment safety

■ **UNIVERSAL COMPATIBILITY**
 Includes the Spider® Universal Adapter Plate which extends up to 17.63" (448 mm) to fit most projector models



Safety Catch Mechanism



Wall Adapter Included with PRG-EXA & PRG-EXB



Model Numbers

PRG-EXA(-S)(-W):	PRG Series Adjustable Projector Ceiling/Wall Mount Kit
PRG-EXB(-S)(-W):	PRG Series Adjustable Projector Ceiling/Wall Mount Kit
PRG-EXC(-S)(-W):	PRG Series Adjustable Projector Ceiling Mount Kit

Product Specifications

	DIMENSIONS (W x H x D) with adapter plate	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
PRG-EXA(-S)(-W)	8.5-17.63" x 8.7"-12.8" x 8.5-17.63" (216-448 x 221-325 x 216-448 mm)	6.81 lb (3.09 kg)	50 lb (22 kg)	Scratch resistant fused epoxy	PRG-EXA: Black
PRG-EXB(-S)(-W)	8.5-17.63" x 12.68"-20.67" x 8.5-17.63" (216-448 x 322-525 x 216-448 mm)	7.17 lb (3.25 kg)			PRG-EXA-S: Silver
PRG-EXC(-S)(-W)	8.5-17.63" x 19.19"-32.91" x 8.5-17.63" (216-448 x 486-836 x 216-448 mm)	7.95 lb (3.61 kg)			PRG-EXA-W: White
					PRG-EXB: Black
					PRG-EXB-S: Silver
					PRG-EXB-W: White
					PRG-EXC: Black
					PRG-EXC-S: Silver
					PRG-EXC-W: White

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
PRG-EXA(-S)(-W)	9.31" x 4.25" x 12.63" (237 x 108 x 321 mm)	7.75 lb (3.52 kg)	PRG-EXA: 735029258476 PRG-EXA-S: 735029258483 PRG-EXA-W: 735029258483	Wall/ceiling plate, adjustable extension columns, ceiling/wall connection brackets, PRG Precision Gear Projector Mount, Spider® Universal Adapter Plate, mounting and projector attachment hardware, assembly instructions	1
PRG-EXB(-S)(-W)	9.31" x 4.25" x 12.63" (237 x 108 x 321 mm)	8.11 lb (3.68 kg)	PRG-EXB: 735029258506 PRG-EXB-S: 735029258513 PRG-EXB-W: 735029258520		
PRG-EXC(-S)(-W)	10" x 4.38" x 19.38" (254 x 111 x 492 mm)	9.28 lb (4.21 kg)	PRG-EXC: 735029258537 PRG-EXC-S: 735029258544 PRG-EXC-W: 735029258551	Ceiling plate, adjustable extension column, ceiling connection bracket, PRG Precision Gear Projector Mount, Spider® Universal Adapter Plate, mounting and projector attachment hardware, assembly instructions	

Accessories

ACC-EXC(S)(W): Extension Column

All dimensions = inch (mm)

PRG-EXA, PRG-EXB, PRG-EXC HEIGHT		
RANGE X	MINIMUM	MAXIMUM
PRG-EXA	1.23" (31 mm)	2.23" (57 mm)
PRG-EXB	1.23" (31 mm)	2.23" (57 mm)
PRG-EXC	1.23" (31 mm)	2.23" (57 mm)
RANGE Y	MINIMUM	MAXIMUM
PRG-EXA	8.7" (221 mm)	12.8" (325 mm)
PRG-EXB	12.68" (322 mm)	20.67" (525 mm)
PRG-EXC	19.13" (486 mm)	32.91" (836 mm)
RANGE Z	MINIMUM	MAXIMUM
PRG-EXA	9.72" (247 mm)	13.86" (352 mm)
PRG-EXB	13.74" (349 mm)	21.73" (552 mm)
PRG-EXC	n/a	n/a

SWIVEL (YAW) 360° (when attached to an extension column), ±15° (when flush mounted)

±20° PITCH

±10° ROLL

ARCHITECTS SPECIFICATIONS

The PRG-Precision Gear Projector Mount shall be a Peerless model PRG-EXA; PRG-EXB; PRG-EXC and shall be located where indicated on the plans. It shall feature Tilt: ±20°, Roll: ±10°, and Swivel: 360° (when attached to an extension column), ±15° swivel (when flush mounted), which enables the image to be perfectly aligned with the screen. It shall be constructed of aluminum alloy finished in black, white, or silver. Assembly and installation shall be done according to instructions provided by the manufacturer.