















FEATURES

- Exceeds output of traditional 30W pinspots while using only 4W
- ✓ Ultra narrow beam optics for optimal long distance throw
- ✓ Magnetic accessory attachment for fillers and diffusers
- ✓ Low voltage and minimal heat for improved safety over incandescent sources
- ✓ Internal constant current driver gives highly efficient and consistent output
- ☑ Dimmable using PWM power input from external constant voltage dimmer (10%-100%)
- Easy installation and reconfiguration
- ✓ Dual polarity input
- Minimal maintenance required over 50,000 hour lamp life
- ✓ Indoor and outdoor use

SPECIFICATIONS

MAX WATTAGE	4.8W
INPUT VOLTAGE	9-15VDC (12VDC nominal)
CURRENT DRAW	400mA @ 12VDC
POWER SUPPLY	Class 2 transformer or battery
BEAM ANGLE	2.7° (diffusable with included filters)
FIELD ANGLE	4.5° (diffusable with included filters)
INGRESS PROTECTION	IP65
LED	Cree XLamp XP-E2
EXTERIOR FINISH	Black anodized aluminum
CERTIFICATION	UL and CE
POWER CONNECTION	2.1mm ID / 5.5mm OD DC jack with screw terminal adapter

SKU NUMBER

Gantom One - Cool White	GT51
Gantom One - Warm White	GT52



