

PORTABLE
PROJECTOR

Qumi Q7 Plus

Super Bright LED HD Multimedia Projector

The Qumi Q7 Plus, the next generation of Vivitek's series of HD LED portable projectors, has a brightness level up to 1000 lumens and weighs only 3.1 pounds. The Qumi Q7 Plus features DLP® Pico chipset and BrilliantColor™ technologies from Texas Instruments and wireless capability. The Qumi's sleek design and connectivity options allows it to be used with a variety of other portable devices, including, but not limited to smart phones, laptops, netbooks and tablets, digital and video cameras. Versatile and portable, the Vivitek Qumi Q7 Plus is perfect for sharing digital content at work and play.

Features

- Native WXGA (1280x800), 720p compatible
- Up to 1000 lumens of brightness and 30,000:1 contrast
- LED light source estimated 30,000 hours of operation
- 4GB built-in memory and USB port for memory expansion to display content without a PC
- 3D-Ready via DLP Link and Blu-Ray 3D playback
- 2D to 3D conversion via HDMI
- Built-in MS Office and Adobe document Viewer
- Multimedia Player for playback of audio, photo, and video files
- MHL device compatibility for streaming of video and audio from a compatible mobile device
- 4 gigabyte of onboard memory plus USB slot for memory expansion



Specifications	
Brightness	Up to 1000 Lumens
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	30,000:1 (Full On/Full Off)
Light Source Life and Type	≈30,000 Hours, LED
Display Type	HD Pico DLP Technology by Texas Instruments
Throw Ratio (±3%)	1.3 to 1.43:1 (Distance/Width)
Image Size (Diagonal)	29" to 107" (0.73 to 2.7 m)
Projection Distance	2.6' to 9.8' (0.8 to 3.0 m)
Zoom Ratio	1.1:1 Manual Zoom/Focus
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset	100% +/-10%
Keystone Correction	± 40° Vertical
3D Ready	Yes (DLP Link) Blu-Ray 3D movie Playback 2D-to-3D conversion
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 91.4 KHz
Vertical Scan Rate	24 ~ 30Hz, 47 ~ 120Hz
Speaker	2W x2 Stereo Surround Speakers
Projection Method	Table Top, Tripod (¼ - 20) or Ceiling (Front or Rear)
Uniformity	85%
File Compatibility	Office Viewer (Doc, XLS, PPT, PDF, TXT) Video (MPEG-4, H.264, Divx™, WMV) Image (JPEG, PNG, BMP, GIF) Audio (MP3, WAV)
Computer Compatibility	1080p, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI x2 (MHL Compatible on HDMI 1), VGA, Composite Video, RCA Stereo-In, Mini-Jack Audio-Out, USB (Type A)
Weight	1.4Kg (3.1 lbs.)
Dimensions (W x H x D)	9.4" x 7.1." x 1.6" (238 x 180 x 40 mm)
Noise Level	33dB/44dB (Eco / Normal mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 141W (Normal Mode), <0.5W (Standby)
Operating Temperature	41 to 95°F (5 to 35°C)
Warranty	2-Year Limited Parts and Labor
Standard Accessories	HDMI Cable, VGA Cable, MHL Cable, Power Cable (US), Carrying Pouch, Remote Control, Lens Cap, User Manual (CD) Quick Start Guide, Warranty Card
Optional Accessories	TBA
UPC	8 14964 33967 6 (White/Q7-WT) 8 14964 33968 3 (Black/Q7-BK)

