



**RDL**® Radio Design Labs®

SPECIALISTS IN PRACTICAL PRECISION ENGINEERING™

## STICK-ON® SERIES

### Model ST-SX4

### 4 Input Audio Switcher

#### ANYWHERE YOU NEED...

- To Select One of Four Audio Sources
- Audio Selection from Remote Location
- Remote Switching from Single Control Pair
- All Solid-State Audio Switching
- Slave Capability for Stereo Switching

#### *You Need The ST-SX4!*



**APPLICATION:** The ST-SX4 is a remote-controllable unbalanced audio source selector in the group of STICK-ON series products by Radio Design Labs. These products are designed for quick, convenient installation and reliable operation in a variety of audio applications.

The ST-SX4 accepts up to Four unbalanced audio sources. Any of these sources may be selected to feed the output, or all sources may be switched off. The output from the ST-SX4 is unbalanced. Control of the module is accomplished through a single input terminal. Connection of a specified resistance between the control input and ground causes the desired input to be switched on. If no control input is connected, the ST-SX4 defaults to input #4. If the control input is shorted to ground, all inputs are switched off.

Use of a single-pair for control allows a minimum of wire to be installed. Installers may use a variety of remote switches; rotary, pushbutton, toggle, etc. The three resistors needed are provided with the module. The ST-SX4 may conveniently be used with the RDL VCA modules to provide both remote switching and remote volume control. In this case, it is necessary to provide only a single-pair-shielded to control both modules (1 conductor to control the ST-SX4, 1 conductor to control the RDL VCA modules, shield to provide control ground path). Two ST-SX4 modules may be used together for stereo switching.

In a wide variety of unbalanced audio switching applications, ST-SX4 affords minimum size, maximum flexibility, low-noise audio clarity and cost-effectiveness for which Radio Design Labs products are known!

Wherever an unbalanced source selector is needed, the ST-SX4 is the ideal choice. Use the ST-SX4 combined with other RDL RACK-UP®, STICK-ON, TX™, or FLAT-PAK™ series products as part of a complete audio/video system.



# STICK-ON® SERIES


## Model ST-SX4

### 4 Input Audio Switcher

## Installation/Operation



EN55103-1 E1-E5; EN55103-2 E1-E4  
 Typical Performance reflects product at publication time exclusive of EMC data, if any, supplied with product. Specifications are subject to change without notice.



### TYPICAL PERFORMANCE

Input/Output Level: -10 dBV  
 Control Input Resistance: 10 kΩ (pullup to +15 Vdc)  
 Gain: Unity  
 Headroom: 23 dB  
 THD+N: < 0.1% Typ 0.05%  
 Frequency Response: 15 Hz - 40 kHz +/- 0.5 dB  
 Input Impedance: 100 kΩ, Unbalanced  
 Output Impedance: < 50 Ω, Unbalanced  
 Crosstalk: Below Noise Floor  
 Off-Channel Attenuation: > 85 dB @ 1 kHz  
 > 80 dB @ 10 kHz  
 > 75 dB @ 20 kHz

Residual Noise: < 70 dB below -10 dBV  
 Control Input: Single terminal to be connected to ground terminal to select desired channel

Input Selected	Resistance Value
None	0 Ω (short to ground)
1	2.7 kΩ
2	6.8 kΩ
3	22.0 kΩ
4	None

Control Output: Slave Output terminal may be attached to other ST-SX4s  
 Power Supply: 24 to 33 Vdc @ 35 mA, Ground-referenced

Radio Design Labs Technical Support Centers

U.S.A. (800) 933-1780, (928) 778-3554; Fax: (928) 778-3506

Europe [NH Amsterdam] (+31) 20-6238 983; Fax: (+31) 20-6225-287