

Tech Spec

ClearSHOT 10 USB

Enterprise-Class, High Definition, Wide-Angle USB 3.0 PTZ Conferencing Camera

Silver/black: 999-9990-000 (North America), 999-9990-001 (international)
White: 999-9990-000W (North America), 999-9990-001W (international)



Features

- Ideal for huddle rooms and small to medium conference rooms in corporate, healthcare, government, and education environments
- Simultaneous uncompressed USB 3.0 and IP (H.264) streaming outputs
- 10X optical zoom, horizontal field of view of 74° in super-wide mode
- 2.14 Megapixel (effective), full HD (native 1080p/60) image sensor
- Precise pan and tilt movements at up to 90° per second
- Presenter-friendly IR remote control
- Universal Video Class (UVC) drivers supported in Windows®, Mac® OS, and Linux operating systems – compatible with most UC conferencing applications
- Full administrative control from your browser via web interface
- Integration-ready Telnet or serial RS-232 control

Back of the Camera



From left to right:

- **12 VDC, 3.0 Amp power connector** – Connect only the power supply shipped with the camera
- **USB 3.0 video device connector** for streaming uncompressed UVC standard video
- **Ethernet RJ-45** for IP streaming, access to web interface and Telnet for camera control
- **RS-232 port** on shielded RJ-45 connector for legacy controllers
- **DIP switches** to set IR frequency, IR on/off, and image flip (camera is invertible)

What's Included

Each ClearSHOT 10 USB camera is shipped with these items:

- Vaddio IR Remote Commander
- 12 VDC, 3.0 A switching power supply and AC cord set (s)
- Thin Profile Wall Mount with mounting hardware
- EZCamera™ control adapter
- USB 3.0 type A to type B cable, 6 ft. (1.8m)
- Quick Start Guide

Basic Connection Diagram



Specifications

Video and Image

Outputs/protocols	IP H.264, RTSP USB 3.0, UVC, YUY2	Aspect ratio	Depends on video resolution
IP video resolutions/frame rates	1080p/30/25/15 720p/60/30/25/15 704x576p/60/30/25/15 720x480p/60/30/25/15 640x480p/60/30/25/15 360p/60/30/25/15 352x288p/60/30/25/15	USB 3.0 video resolutions/frame rates	1080p/30/15 720p/60/30/15
		USB 2.0 and 3.0 video resolutions/frame rates All USB resolutions uncompressed	960x540p/30/15 848x480p/30/15 360p/60/30/15 424x240p/30/15 320x240p/30/15 180p/30/15
Streaming	IP (H.264), RTSP + USB 3.0 (UVC) IP and USB streams are simultaneous and can be at differing resolutions.		

Camera

Image device	1/2.8-Type Exmor CMOS sensor		
Pan angle and speed	± 170°, up to 90°/sec	Tilt angle and speed	+90° -30°, up to 90°/sec
Lens and horizontal FOV	10X Optical zoom, 67.0° wide to 7.6° tele, f=3.8mm to 38mm, F1.8 to F3.4 Super-wide: 11X Optical zoom, 74° wide to 7.6° tele, f=3.8mm to 41.8mm, F1.8 to F3.4		
Minimum working distance	10mm (wide), 1.0m (tele)	Minimum illumination	Recommended: >100 lux
Pixels	2.14 million (effective)	Aperture/detail	16 steps (via all remote management interfaces)
Gain	Auto or manual		
Backlight compensation	On or off	White balance	Auto, manual, One-Push
Focusing system	Auto or manual	Noise reduction	On or off
Sync system	Internal	S/N ratio	Over 50 dB
Power	12 VDC, 3.0 Amp switching power supply		
Remote management	Web interface (Chrome, Firefox, Safari, Internet Explorer 8 through 11), Telnet, RS-232 API (modified VISCA)		

Physical and Environmental

Height	6.3" (163mm)	Operating temperature	0°C to +40°C (32°F to 104°F)
Width	6.1" (155mm)	Operating humidity	20% to 80% RH
Depth	5.5" (145mm)	Storage temperature	-5°C to +60°C (23°F to 140°F)
Weight	3.0 lbs.(1.36 kg)	Storage humidity	20% to 80% RH

Specifications are subject to change without notice.



Copyright © 2015 Vaddio – All rights reserved. Reproduction in whole or part without written permission is prohibited. Specifications and pricing are subject to change without notice. Vaddio and ClearSHOT are trademarks of Vaddio. All other trademarks are the property of their respective owners.

Learn more about our cameras, audio devices and controllers at www.vaddio.com.