

QUATTRO



A compact, four-port version of our popular DMX management nodes. Power-over-Ethernet operation makes it ideal for truss-mounted locations.

FEATURES

- Four DMX512 ports, individually configurable
- DMX routing on a universe or channel-by-channel basis, merged or prioritized
- Rugged cast aluminum housing
- Address up to 64000 universes, depending on the protocol chosen
- Supports the following Ethernet protocols:
 - Strand Shownet
 - Pathport Protocol
 - ArtNet
 - E1.31 Streaming ACN (sACN/Net3)
 - Ki-Net
- DMX output speed and signal loss behavior are user-selectable
- LCD/Encoder knob provide front panel configuration and status reporting
- Compact size - 2 nodes can fit side-by-side in 1RU of rack space
- Uses Power-over-Ethernet (PoE) or an auxiliary 24VDC supply (by others)
- Rackmount ears included

MODEL DESCRIPTION

- 6311** Pathport Quattro 4-port, rear XLR5F
- 6312** Pathport Quattro 4-port, rear terminal strip
- 6316** Pathport Quattro 4-port, rear RJ45 Ethercon

ACCESSORIES

- 6001** In-Line PoE Injector
- 9004** Truss Mount Adaptor

Pathport Manager Configuration Software is available as a free download from our website

