



LED-1708HDR

This LED-backlit rack monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

Related Products

- LED-1708HD
- LED-1708HDL
- LED-1908HD
- LED-1908HDL
- LED-1908HDR
- LED-1908HDVB
- LED-1908IP67
- LED-1908IP67TS

Specifications

Mount	Rack mount: 8RU
HD Compatible	Yes
Anti Glare Coating	Yes
Selectable Color Temp.	Yes
Case	Durable Metal
Native Aspect Ratio	5:4
Visible Screen Size (WH)	340 x 272mm / 13.4" x 10.7
Resolution	1280(H) x 1024(V)
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.264(H) x 0.264(V)
Color Depth	16.7 M
Number of Pixels	1,310,720
Response Time	5 ms
Audio Power / Speakers	1.5W x 2
Viewing Angle (L/R/T/B)	85/85/80/80
Pixel Configuration	Stripe
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Dimensions w/o	8RU x 2.9"
Operating Temp/Humidity	32 ~ 104°F / 0 ~ 40°C, 10% ~
Power Requirements	DC 12V (AC100~240)[50/60]
Composite	BNC IN/OUT x 2
PC	VGA input 15 pin D-sub
HDMI / DVI / RS-232	Yes/No/No
Audio	L/R RCA audio inputs, 3.5 PC
Power	2.1mm DC IN jack
Weight	Net 5.4 Kg / 11.9 lbs. Gross 8
GSA	