



LED-1003HD

This 9.7" LED-backlit monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution megapixel imagery.

Benefits

- LED backlight: brighter picture using less power
- Wide viewing angle
- Excellent contrast ratio
- Very fast response time
- Image enhancing: 3D Interlace comb filter, DNR, 4H filter
- Durable metal case

Accessories

- DC-1500: Factory approved car cord
- HM-401: Under-cabinet hinge mount
- WM-31: Wall mount bracket (fixed)
- WM-302: Wall mount with swing arm & 4-way adjustable

Related Products

- LED-1002HD2: Dual 9.7" monitors in a rack-mount
- LED-1003HDL: Flush-mount
- LED-1003HDX: Free-standing with no front controls
- LED-1003HDLX: Flush-mount with no front controls

Specifications

Mount	VESA 75x75mm and 100x100mm; ¼ - 20 pad top and bottom; Removable Deskstand
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Metal
Native Aspect Ratio	4:3
Visible Screen Size (WH)	7.8" x 5.9" / 197.6 x 148.8mm
Resolution	1024(H) x 768(V)
Brightness Rating	400 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
PC Compatibility	Yes
Dot Pitch	0.192 (H) x 0.192 (V)mm
Color Depth	262,144
Number of Pixels	786,432
Response Time	2ms / 2ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	89/89/89/89 degrees
3D Comb Filter	3D Interlace comb DNR, 4H filter
Dimensions w/ Deskstand	8.8" x 7.7" x 6.3" / 223 x 196.4 x 160mm
Dimensions	8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Power Requirements	12VDC; 2A; Negative Ground
Power Consumption	15 Watts (Max)
Composite	x2 BNC Inputs / Outputs
PC	x1 15-pin mini D-sub Input
HDMI	x1 Input
Audio	x1 RCA L/R Input; x1 3.5mm PC Input
Power	x1 2.1mm DC Input
Weight	Net: 2.55 lbs / 1.2 kg; Gross: 4.6 lbs / 2.1 kg
GSA	Yes

Specifications subject to change.