



LED-566HDMx3

Three 5.6" rack mount monitors feature the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on these monitors, and they are the best match for displaying higher resolution megapixel imagery.

Benefits

- LED backlight: brighter picture using less power
- Switchable 4:3 and 16:9 aspect ratios
- Multi-featured: Underscan, Blue Gun, RGB adjustable
- Monochrome and color peaking modes for fine control optimizing focus
- DSLR Scaling when connected to a still photography camera
- On-board memory retains last input source when power is Off
- Sturdy metal housing
- Automatic scaling of signal resolution
- Excellent electromagnetic shielding



Specifications	
Mount	Rack Mount (3RU)
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable Metal
Electromagnetic Shielding	Yes
Native Aspect Ratio	4:3
Visible Screen Size (WH)	4.4" x 3.3" / 112.9 x 84.7mm
Resolution	640 x 480 (displays 480i/p ~ 1080i/p)
Brightness Rating	350 cd/m ² (Nit)
Contrast Ratio	500:1
Back Light	LED (20K)
Dot Pitch	0.0588mm x 0.1764mm
Color Depth	5600K ~ 6500K (User Adjustable)
Number of Pixels	307,200
Response Time	10/15ms (Rising/Falling)
Audio Power	2 Watts
Viewing Angle (L/R/T/B)	70/70/50/70 degrees
Dimensions	18.89" x 5.24" x 2.36" / 480 x 133 x 60mm
Operating Temp	-4 ~ 140°F / -20 ~ 60°C
Humidity	20% ~ 80%
Auto Power On	Yes
Mirror Image	Yes
Signal Resolution Scaling	Automatic
NTSC/PAL Auto-sensing	Yes
HDMI	x3 Inputs
Composite	x3 BNC Inputs / Outputs
Audio	x3 3.5mm Inputs; x3 3.5mm Outputs
Power	x1 2.1mm DC Input
Power Requirements	11VDC ~ 14VDC; 2A; Positive Pin; Negative Ground
Power Consumption	15 Watts
Weight	Net: 4 lbs / 1.81 kg

Specifications subject to change.