



## LED-709HDML

This flush-mount, high-definition monitor with touch-screen capability is designed for in-wall video placements and used in a variety of transportation, security, and AV applications.

### Benefits

- LED backlight: brighter picture using less power
- Displays HD signals (1080i/p and 720p)
- 16:9 native aspect ratio
- Built-in 5-wire resistive touch screen when viewing a VGA source

### Related Products

- LED-709HD: 7" Field LCD Monitor
- LED-709HDM: Durable Metal LCD Monitor
- LED-709HD2: Rack-Mount LCD Monitor

### Specifications

<b>Mount</b>	Flush Mount
<b>HD Compatible</b>	Yes (displays 1080p)
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable Metal
<b>IR Remote Control</b>	No
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	6" x 3.4" / 154.08 x 85.92mm
<b>Resolution</b>	1024 x 600
<b>Brightness Rating</b>	250 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	700:1
<b>Back Light</b>	LED (20K)
<b>Dot Pitch</b>	0.0642(H) x 0.1790(V) mm
<b>Number of Pixels</b>	1.2M
<b>Response Time</b>	25ms (Rising/Falling)
<b>Viewing Angle (L/R/T/B)</b>	70/70/50/70 degrees
<b>Dimensions</b>	9.2" x 10.6" x 1.5" / 234 x 270 x 38mm
<b>Operating Temp</b>	-4 ~ 158°F / -20 ~ 70°C
<b>Touchscreen</b>	x1 USB cable with VGA only; 5-wire resistive
<b>HDMI</b>	x1 Input
<b>Composite</b>	x2 RCA Inputs on cable with 3.5mm jack
<b>VGA</b>	x1 15-pin D-sub Input
<b>Power</b>	x1 2.1mm DC Input
<b>Power Requirements</b>	10 VDC to 27 VDC Input; 2A + pin; Negative Ground
<b>Power Consumption</b>	24 Watts (Max)
<b>Weight</b>	Net: 2.5 lbs / 1.13 kg; Gross: 4.3 lbs / 1.95 kg

Specifications subject to change.