



## DTW BLINDER 350 IP™

SKU# DTW350

The IP65 rated DTW Blinder 350 IP™ is a 350W LED blinder luminaire featuring (2) high powered 175W 2-in-1 Warm White / Amber COB LEDs, pixel control, each pixel producing a 25° narrow beam angle with included fresnel lens filters or a 78° wide beam with lens removed, a unique "Dim-to-Warm" function that allows dimming from 1,800K to 3,200K, manual adjustable pan focus, electronic strobe and variable dimming curve effects, flicker free operation for TV and Film, RDM (Remote Device Management), IP rated 5pin DMX and powerCON TRUE1 in/out connections, LCD menu display with 4 touch button control panel, integrated yoke and side mounting brackets, and a multi-voltage universal auto switching power supply (100-250v).

### FEATURES

**IP65 Rated 350W COB LED Blinder Luminaire**

**(2) 175W 2-in-1 Warm White / Amber COB LEDs**

**Pixel Control**

**25° Narrow Beam with included Fresnel Lens**

**78° Wide Beam with Fresnel Lens Removed**

**Dim-to-Warm Channel Control (1,800 - 3,200K)**

**RDM (Remote Device Management)**

**Flicker Free Operation for Broadcast TV and FILM**

**Rugged Die-Cast Aluminum Exterior**

**Multiple Unit Power Linking**



## PRODUCT SPECIFICATIONS

### SOURCE

(2) 175W 2-in-1 Warm White / Amber COB LEDs  
50,000 Hour Average LED Life\*

\*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, and Usage Patterns (On-Off Cycling, Control and Dimming).

### PHOTOMETRIC DATA

6,269 LUX 582 FC @9.8' (3m) (25° Fresnel Lens Full ON)  
871 LUX 81 FC @9.8' (3m) (78° Full ON)

### EFFECTS

Pixel Control

25° Narrow Beam Angle with Included Fresnel Lens

78° Wide Beam Angle with Fresnel Lens Removed

Unique Dim-to-Warm Channel Control (1.800K - 3.200K)

Electronic Strobe and Variable Dimming Curves

### COLOR

Warm White / Amber

### CONTROL / CONNECTIONS

(9) DMX Channel Modes (9 Total Channels)

RDM (Remote Device Management)

(4) Button TouchControl Panel

IP Rated 5pin DMX In/Out

powerCON TRUE 1 In/Out

### SIZE / WEIGHT

Length: 15.74" (400mm)

Width: 9.46" (240.5mm)

Vertical Height: 9.64" (245mm)

Weight: 18.0 lbs. (8.2 kg)

### ELECTRICAL / THERMAL

AC 110-240V - 50/60Hz

310W Max Power Consumption

Multiple Unit Power Linking

5°F to 113°F (-15°C to 45°C)

### INCLUDED ITEMS

(2) 25° Narrow Beam Fresnel Lens

powerCON TRUE1 Power Cable

### APPROVALS / RATINGS



## OPTIONAL ACCESSORIES

ORDER CODE	ITEM
<b>NARROW CLAMP</b>	PRO 2" Wrap Around Clamp
<b>8050000053</b>	Omega Bracket (107mm)
<b>NEU088</b>	3 ft. (1m) PowerCON TRUE1 Power Link Cable
	Additional cable lengths available

## PHOTOMETRIC DATA

### 25° Beam Diameter with Fresnel Lens

	3 m	9.8 ft	4 m	13.1 ft	5 m	16.4 ft
<b>25° Beam Diameter</b>	1.33	4.4	1.77	5.8	2.21	7.3
	lux	fc	lux	fc	lux	fc
<b>WW LEDs 3,100K</b>	3,447	320	1,992	185	1,321	123
<b>AMBER LEDs 1,400K</b>	352	33	213	20	143	13
<b>FULL ON 2,940K</b>	6,269	582	3,417	317	2,424	225

### 78° Beam Diameter No Fresnel Lens

	3 m	9.8 ft	4 m	13.1 ft	5 m	16.4 ft
<b>78° Beam Diameter</b>	4.99	16.4	6.67	21.9	8.21	26.9
	lux	fc	lux	fc	lux	fc
<b>WW LEDs 3,100K</b>	561	52	333	31	235	22
<b>AMBER LEDs 1,400K</b>	64	6	45	4	34	3
<b>FULL ON 2,940K</b>	871	81	548	51	364	34

## DIMENSIONAL DIAGRAMS

