



**C208**

8/2 Unshielded TC  
Large Venue Speaker Distribution

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	8
• Conductor Stranding	65x26
• Conductor Type	Bare copper
• Nominal DCR	0.7 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thickness	0.038 in
• Insulation Color Code	1. Black 2.White
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.062 in
Nominal Cable O.D.	0.498 in
Plenum	No
NEC UL Rating	TC
RoHS Compliant	Yes
Pull Tension	410 lbs
Bend Radius	4.482 in

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	600



**C208**

8/2 Unshielded TC  
Large Venue Speaker Distribution

**Related Products**

RELATED PRODUCTS	-