

Strobe™ / Strobe Lite™



Power is everything! The Strobe from Robe could not be anything but THE brightest, best value, most sophisticated strobe-blinder effects unit on the market.

Ultimately controllable, configurable and arrayable. Super fast bursts of high powered pulses can be adjusted in frequency, duration and intensity, optically harnessed from the 120x High Power White LED chips. Easy to rig individually or in multiples and easy to program, using direct segment control or the pre-defined macros. Fitted with the standard Robe RNS touch screen system with DMX, RDM, Art-Net, MA Net and sACN protocols. Optional wireless DMX module.

- **Light source**

120x High Power White LED chips

- **Light output**

5.600 lux @ 5 m / 48.500 lm

- **Zoom range**

32° (at 1/2 beam), 60° (at 1/10 beam)

- **Effects**

12 zones control, continuous full power operation, strobe effects

technical

specification

- **Source**

- Light Source Type: 120x High Power White LED chips
- CCT: 6.000 K
- LED Life Expectancy: Minimum 60 000 hours
- Typical Lumen Maintenance: 70% @ 60 000 hours

- **Optical System and Effects**

- High efficient component optics
- Beam Angle: 32° (at 1/2 beam), 60° (at 1/10 beam)
- Individual control: 12 segments (3 lines and 4 columns)
- Strobe duration: 13-860 ms
- Strobe rate: 0.3-30 Hz
- Blinder effect: Continuous full power operation with high resolution dimmer
- High Resolution Dimmer (Internal 18 bit): 8 or 16 bit
- Strobe effects: Ramp up, ramp down, ramp up-down, random flash, single flash

- **Control and Programming**

- Setting & Addressing: Robe Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Optional wireless version available: CRMX™ technology from Lumen Radio
- Control Channels: 8, 20, 3, 4
- Protocol Modes: 4
- Programs: 3 editable programs up to 88 steps
- Stand-alone operation
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC Ethernet Port: Art-Net protocol, ready for

ACN

- Data in/out: Locking 5-pin XLR
- Built in analyser for easy fault finding

• Thermal Specification

- Maximum Ambient Temperature: 45° C (113° F)
- Maximum Housing Temperature: 75° C (167°C)

• Movement

- Tilt adjustment: Manual

• Electrical Specification

- Electronic auto-ranging
- Input Voltage Range: 100-240 V, 50/60 Hz
- Power Consumption: 660 W
- Power Connector: Neutrik PowerCon

• Approvals

- CE Compliant
- cETLus Compliant

• Mechanical Specification

- Height (U-holder vertically): 350mm (13.8")
- Width: 315 mm (12.4")
- Depth: 300 mm (11,8")
- Weight: 14.3 kg (31.5 lbs)
- Ingress protection: IP22

• Rigging

- Mounting Points: 1 pair of 1-turn locks
- Multipoint segment locking for big trusses instalations
- Omega Brackets: 2x Omega bracket with 1-turn quick locks

• Accessories

- Optional: floor stand, barndoor, frame adaptor, gel frame, stacker

