

Model Name	HS-2850
Product Name	HD/SD 12-Channel Portable Video Studio
Video Standard	HD & SD
Video Format	3G/HD/SD input: 1080i 50/59.94/60Hz 1080p 25/30/59.94/60Hz HD Output: 1080i 50/59.94/60Hz SD: 576i 50Hz, 480i 59.94Hz
Input Routable / Crosspoint	All 12, repeatable
Video Input	Standard: 8x SDI, 2x HDMI Max: 12x SDI, 3x HDMI
Computer Graphic Interface	Max 3 via HDMI
Down-converted output	2x SDI
Video output	3x SDI assignable: PGM, PVW, AUX & Clean Out 1x HDMI assignable: PGM & multi-view
Audio input	4x Balanced XLR
Audio output	2x Balanced XLR
Embedded audio support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	Up to 8 frames
A+V switching	Yes
USK	N/A
DSK	2x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Built-in Audio Mixer	N/A
Built-in Monitor Display	17.3" HD TFT LED backlit, 1600x900 pix
Built-in Intercom & Tally	8 channels (4 belt-packs incl.)
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	19.6 Lbs (9 Kg), Reinforce Plastic Case
Accessory	CB-22H/23H/46/47/50