

## Panel

Diagonal Size	65	Type
Resolution	3840*2160 (4K UHD)	Pixel Pitch(mm)
Active Display Area(mm)	1438.48(H) x 814.52(V)	Brightness(Typ.)
Contrast Ratio	4000:01:00	Viewing Angle(H/V)
Response Time(G-to-G)	8ms (Typ)	Display Colors
Color Gamut	72%	Haze

## Display

Dynamic C/R	Mega	H-Scanning Frequency
V-Scanning Frequency	48 ~ 75HZ	Maximum Pixel Frequency

## Display

Speaker Type	Built in Speaker(10W + 10W)
--------------	-----------------------------

## Connectivity

Input	RGB	DVI-D, Display Port 1.2 (1)
	Video	HDMI 2.0 (2)
	HDCP	HDCP2.2
	Audio	Stereo mini Jack, DVI, HDMI
	Usb	USB 2.0 x 2
Output	RGB	HDMI 2.0 (Loop-out)
	Video	N/A
	Audio	Stereo mini Jack
	Power Out	N/A
External Control		RS232C(in/out), RJ45
External Sensor		IR
Tuner		N/A

## Power

Type	Internal	
Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60Hz	
Power Consumption	Max[W/h]	
	Typical[W/h]	
	BTU(Max)	N/A

	<b>Sleep mode</b>	less than 0.5W
	<b>Off mode</b>	less than 0.5W

## Mechanical Specification

<b>Dimension (mm)</b>	<b>Set</b>	1456.1 x 835.6 x 37.5
	<b>Package</b>	1571 X 956 X 212
<b>Weight (kg)</b>	<b>Set</b>	
	<b>Package</b>	
<b>VESA Mount (mm)</b>		400x400
<b>Mounting Hole</b>		N/A
<b>Protection Glass</b>		N/A
<b>Stand Type</b>		Foot Stand (Optional)
<b>Media Player Option Type</b>		N/A
<b>Bezel Width (mm)</b>		12.0/12.0/12.0

## Operation

<b>Recommended Usage Hours</b>	24/7	
<b>Operating Temperature</b>	0.0 °C ~ 40.0 °C	<b>Humidity</b>

## Feature

<b>Key Features</b>		UHD Signage Display Slim & Light 5.0
<b>Special Features</b>		H/W : Temperature Sensor, Pivoting (Temperature Keeping), Built in Speaker(10W), Video Chain(HDCP2.2:4EA, HDCP1.4:7EA), Video Switching & Recovery, LFD Horizontal Sync (Initial Setting)
<b>Internal Player</b>	<b>Processor</b>	Coretex A72 1.7GHz Quad-Core
	<b>On-Chip Cache Memory</b>	L1 Instruction Cache : 48KB L1 I-Cache
	<b>Clock Speed</b>	1.7GHz Quad-Core CPU
	<b>Main Memory Interface</b>	3GB 3ch 64bit LPDDR4 1.6GHz
	<b>Graphics</b>	2D & 3D Graphic Accelerator Display Resolution : 3840x2160p
	<b>Storage (FDM)</b>	8GB (3.88GB Occupied by O/S, 4.12GB Available)
	<b>Multimedia</b>	Video Decoder - MPEG 1/2/4, H.264, H.265, AVS/AVS+, MVC - VP8, VP9, HEVC, AAC, AC4, DD, MP3 and etc
	<b>IO Ports</b>	USB 2.0
	<b>Operating System</b>	Tizen 3.0 (VDLinux)

## Certification

<b>Safety</b>	60950-1
<b>EMC</b>	Class A

## Accessory

<b>Included</b>		Quick Setup Guide, Warranty C Batteries
<b>Optional</b>	<b>Stand</b>	STN-L6500E
	<b>Mount</b>	WMN6575SD
	<b>Specialty</b>	CLM450D

## Media Player

<b>Media Player</b>	SBB
---------------------	-----




22.8
32.4

10.0 % ~ 80.0 %

ht Signage with Built-in MagicInfo S5, SSSP
ot Display, Clock Battery(168hrs Clock 2ch), Video Wall Daisy EA), IP5x, Wi-Fi/BT S/W : Auto Source ne UI, Button Lock, Hot key option, Plug&Play
: CPU
Data Cache : 32KB L2 Cache : 2MB
ata Format : 32bpp Output resolution :
4.12GB Available)
1.263, H.264/AVC - UHD H.264/AVC, VC-1, VC, JPEG Audio DSP(Decoder) - MPEG, AC3,


ard, Power Cord, Remote Controller,
