



Configuration:

LS-48-216 Listen Premiere Level II Stationary RF System (216 MHz)
 LS-48-072 Listen Premiere Level II Stationary RF System (72 MHz)

Product Overview:

By combining our LT-800 transmitter and LR-400 receivers on the 216 MHz band, the LS-48 Premiere Level II Stationary RF System is a complete solution for single-channel assistive listening applications. The full system provides a solid foundation for meeting legislative requirements while offering a high-end listening experience. Additional equipment, including the universal antenna kit, signage kit, and more make the LS-48 a complete package for immediately incorporating assistive listening into your venue and meeting the needs of your clients, visitors, or customers.

Highlights:

- LT-800 transmitter and LR-400 receivers provide a solid foundation for your assistive listening system
- Industry-leading audio quality thanks to receivers with an 80 dB signal-to-noise ratio (SNR)
- Extended transmission range for complete coverage in larger venues
- 57 digital channels available for flexibility and a reliable connection between transmitter and receiver
- Look & Listen (TM) LCD screens on each receiver displays channel selection, battery status, and signal strength
- Backed by Listen Technologies’ limited lifetime warranty and hassle-free support

Includes: One (1) LT-800-216-01 RF Transmitter (216 MHz)
 One (1) LA-122 Universal Antenna Kit (72 MHz and 216 MHz)
 One (1) LA-326 Universal Rack Mounting Kit
 Four (4) LR-400-216 Portable Display RF Receiver (216 MHz)
 Four (4) LA-164 Ear Speaker
 Two (2) LA-166 Neck Loop
 One (1) LPT-A107-B Dual RCA to Dual RCA Cable 2 m (6.6 ft.)
 Four (4) LA-361 High Capacity AA Alkaline Batteries (2)
 One (1) LA-304 Assistive Listening Notification Signage Kit

Product Specification: Listen Premiere Level II Stationary RF System (216 MHz)	
Physical	
Shipping Weight	24.0 (10.3)