

Battery Run Time Chart

*Run time in Minutes

On-Camera	Litepanels Lighting Range				Anton/Bauer Battery Type						
	Part Number	Wattage draw (W)	Amp draw (@13V)	Voltage range (VDC)	NP-F774 30 Watt/hr	NP-F976 47 Watt/hr	Dionic HC /Digital/Cine 90 Watt/hr	Hytron 100 100 Watt/hr	Digital 150/Cine 150 150 Watt/hr	Digital 190 190Watt/hr	Hytron 140 140Watt/hr
Croma 2	MLCROMA2	14	2.2-0.8	6.5-18	125 ^{·1}	200 ^{·1}	385 ^{·2}	425 ^{·3}	640 ^{·2}	810 ^{·2}	600 ^{·3}
MicroPro 2	MLMICROPRO2	14	2.2-0.8	6.5-18	125 ^{·1}	200 ^{·1}	385 ^{·2}	425 ^{·3}	640 ^{·2}	810 ^{·2}	600 ^{·3}
Spectra 2	MLSPECTRA2	8	1.2-2.3	6.5-18	225 ^{·4}	350 ^{·4}	675 ^{·2}	750 ^{·3}	1,125 ^{·2}	1,425 ^{·2}	1,050 ^{·3}
Brick Bi-Color	915-1003	18	1.5-1.1	12-17	●	●	300	330	500	630	465

*1 Include L-Series Battery Plate (MLBATTADT-L7.2V) *2 D-Tap* Power Cable (900-6104) *3QRC-LG Gold Mount* Stand Mount (8375-0176) with D-Tap* Power Cable (900-6104) *4 L-Series Battery Plate (MLBATTADT-L7.2V)

LED Panels	Litepanels Lighting Range				Anton/Bauer Battery Type								
	Part Number	Wattage draw (W)	Amp draw (@13V)	Voltage range (VDC)	NP-F774 30 Watt/hr	NP-F976 47 Watt/hr	Dionic HC /Digital/Cine 90 Watt/hr	Hytron 100 100Watt/hr	Digital 150/Cine 150 150 Watt/hr	Digital 190 190 Watt/hr	Hytron 140 140Watt/hr	VCLX 560 Watt/hr	VCLX/2 280 Watt/hr
Lykos Daylight	MLL1500-D	23	3.5-13	6.5-18	75 ^{·1}	120 ^{·1}	120 ^{·1}	260 ^{·3}	425 ^{·3}	640 ^{·2}	365 ^{·2}	●	●
Lykos Bi-Color	MLL1300-BI	23	3.5-1.3	6.5-18	75 ^{·1}	120 ^{·1}	120 ^{·1}	260 ^{·3}	425 ^{·3}	640 ^{·2}	365 ^{·2}	●	●
ASTRA													
Astra 3x Daylight	935-2021	55	4.1-1.65	12.5-31	●	●	98 ^{·4}	109 ^{·4}	164 ^{·4}	207 ^{·4}	153 ^{·4}	611 ^{·5}	305 ^{·5}
Astra 3x Bi-Color	935-2023	55	4.1-1.65	12.5-31	●	●	98 ^{·4}	109 ^{·4}	164 ^{·4}	207 ^{·4}	153 ^{·4}	611 ^{·5}	305 ^{·5}
Astra 6x Daylight	935-1021	105	8.5-3.42	12.5-31	●	●	51 ^{·4}	57 ^{·4}	86 ^{·4}	109 ^{·4}	80 ^{·4}	320 ^{·5}	160 ^{·5}
Astra 6x Bi-Color	935-1023	105	8.5-3.42	12.5-31	●	●	51 ^{·4}	57 ^{·4}	86 ^{·4}	109 ^{·4}	80 ^{·4}	320 ^{·5}	160 ^{·5}
Astra Soft Bi-Color	935-5021	105	8.5-3.42	12.5-31	●	●	51 ^{·4}	57 ^{·4}	86 ^{·4}	109 ^{·4}	80 ^{·4}	320 ^{·5}	160 ^{·5}
HILIO													
Hilio D12 Daylight	907-2001	310	7.6-5.2	41-60	No Anton/Bauer Mobile Power Solution Available								
Hilio D12 Daylight	907-2003	310	7.6-5.2	41-60	No Anton/Bauer Mobile Power Solution Available								
GEMINI													
Gemini		325	11.6	28	●	●	n/a	n/a	n/a	n/a	n/a	n/a	n/a

*1 Include L-Series Battery Plate (MLBATTADT-L7.2V) *2 D-Tap* Power Cable (900-6104) *3QRC-LG Gold Mount* Stand Mount (8375-0176) with D-Tap* Power Cable (900-6104)
 4 Astra Gold Mount Battery Plate with P-Tap to 3-Pin XLR Cable (900-3507) or Astra V-Mount Battery Plate with P-Tap to 3-Pin Cable (900-3508) (VCLX) *5 Included 3-Pin XLR Power Cable (VCLX) *6 (2) 14.4V battery plate (Gold Mount and V-Mou options Coming Soon)

LED Fresnel	Litepanels Lighting Range				Anton/Bauer Battery Type								
	Part Number	Wattage draw (W)	Amp draw (@13V)	Voltage range (VDC)	Dionic HC/Digital/Cine 90 90 Watt/hr	Hytron 100 100 Watt/hr	Digital 150/Cine 150 150 Watt/hr	Digital 190 190 Watt/hr	Hytron 140 140Watt/hr	VCLX 560Watt/hr	VCLX/2 280 Watt/hr		
HILIO													
Inca 4	906-4003	36	3.10-1.18	11.6-30.4	150 ^{·1}	165 ^{·1}	250 ^{·1}	315 ^{·1}	230 ^{·1}	930 ^{·2}	460 ^{·2}		
Inca 6	906-2003	95	8.19-2.98	11.6-31.9	55 ^{·3}	60 ^{·3}	90 ^{·3}	120 ^{·3}	85 ^{·3}	930 ^{·2}	460 ^{·2}		
Inca 9	906-5003	172	4.3-2.9	40-60	No Anton/Bauer Mobile Power Solution Available								
Inca 12	906-2003	320	8.0-5.33	40-60	No Anton/Bauer Mobile Power Solution Available								
SOLA / Daylight													
Caliber	909-1001	13.1	2.38-1.01	5.5-13	415 ^{·6}	460 ^{·6}	690 ^{·6}	875 ^{·6}	645 ^{·6}	●	●		
Sola ENG	906-1002	27	2.7-1.35	10-20	200 ^{·5}	220 ^{·6}	330 ^{·5}	875 ^{·6}	645 ^{·6}	●	●		
Sola 4+	906-4024	53	3.10-1.18	11.6-30.4	102 ^{·1}	113 ^{·1}	170 ^{·1}	215 ^{·1}	158 ^{·1}	634 ^{·2}	317 ^{·2}		
Sola 6+	906-2024	104	8.19-2.98	11.6-31.9	52 ^{·3}	58 ^{·3}	87 ^{·3}	110 ^{·3}	81 ^{·3}	323 ^{·4}	162 ^{·4}		
Sola 9	906-5001	172	4.3-2.9	40-60	No Anton/Bauer Mobile Power Solution Available								
Sola 12	906-3001	320	8.0-5.33	40-60	No Anton/Bauer Mobile Power Solution Available								

1 QRC-LG Gold Mount Stand Mount (8375-0176) PowerTap 36 XLR 4-Pin (8075-0135) with 7ft PowerTap Ext (8075-0010) *2 Included 4-Pin XLR Power Cable *3 QRC-LG Gold Mount* Stand Mount (8375-0176) 3-Pin XLR to 2-Pin D-Tap* Power Cable (900-0024) and 7ft PowerTap Ext (8075-0010)
 *4 Included 3-Pin XLR Power Cable *5 Included D-Tap* Cable *6 3rd party D-Tap* Cable
 4 Astra Gold Mount Battery Plate with P-Tap to 3-Pin XLR Cable (900-3507) or Astra V-Mount Battery Plate with P-Tap to 3-Pin Cable (900-3508) (VCLX)