



2 x 10 Fader Wing



2 x 20 Fader Wing

GENERAL INFORMATION

The compact Universal Fader Wings can connect to an Eos Ti®, Gio®, Gio @5 or Ion console to provide more physical playbacks or to a Congo® jr console to provide access to 20 or 40 Master Playbacks. The connection may be made via USB cable, or the wing(s) may be physically connected to either side of an Ion or Congo jr console.

APPLICATIONS

- Any situation requiring additional fader control from:
 - An Eos Ti, Gio, Gio @5 Ion or Congo consoles
 - An Eos/Ion Remote Processor Unit
 - A Cobalt Light Server
 - A Net3 Remote Video Interface or RVI3 Remote Video Interface
 - A PC operating ETCnomad™ for Eos or Cobalt
 - An ETCnomad Puck™

FEATURES

- Two rows of 10 faders, two rows of 20 faders or one row of 20 faders
- Integral LCD display(s) on the Wings only, for identification and labeling functions
- USB connectivity to console, RPU/Light Server, RVI or PC

ORDERING INFORMATION

Universal Fader Wing

MODEL	DESCRIPTION
FADW 2 x 10	2x10 Fader Wing
FADW 2 x 20	2x20 Fader Wing

Ships with

- Universal 12V power supply with Wings
- USB A-to-B cable
- Documentation

Note: The Universal Fader Wings are not compatible with ETCnomad on an Apple computer.

SPECIFICATIONS

PHYSICAL

- 20/40 45mm faders
 - 40/80 keys for various functions
 - Integral LCD display(s) for identification and labeling (Wings only)

INTERFACES

- USB Multipurpose bus

COMPATIBILITY

- In Eos Family control systems:
 - Eos
 - Eos Ti
 - Gio
 - Gio @5
 - Ion
 - Eos Remote Processor Units (Eos RPU3)
 - Ion Remote Processor Units (Ion RPU)
 - Remote Video Interface (RVI)
 - Remote Video Interface 3 (RVI3)
 - ETCnomad and ETCnomad Puck (PC)
- In Cobalt Family control systems:
 - Congo jr console
 - Cobalt 20/10
 - Congo jr
 - Cobalt Light Server
 - Net3 Remote Video Interface (RVI)
 - ETCnomad (PC)

ELECTRICAL

- When rigidly connected to Ion or Congo jr, unit powered by console
- When connected with external USB:
 - 2 x 20 = 10-watt power consumption maximum
 - 2 x 10 = 5-watt power consumption maximum
 - 8 to 28Vdc external power supply (included)
 - 1 x 20 = 50-200mA at 5V

PHYSICAL


Universal Fader Wing Weights*

MODEL	WEIGHT		SHIPPING WEIGHT	
	lbs	kgs	lbs	kgs
FADW 2 x 10	6.5	2.95	8	3.65
FADW 2 x 20	12	5.5	15	7


Universal Fader Wing Dimensions*

MODEL	HEIGHT		WIDTH		DEPTH	
	inches	mm	inches	mm	inches	mm
FADW 2 x 10	5.25	133	9.45	240	15.93	405
FADW 2 x 20	5.25	133	17.89	454	15.93	405


*Weights and dimensions typical



2 x 10 Fader Wing



2 x 20 Fader Wing



Corporate Headquarters • 3031 Pleasant View Rd, PO Box 620979, Middleton WI 53562 0979 USA • +1 608 831 4116

London, UK • Unit 26-28, Victoria Industrial Estate, Victoria Road, London W3 6UU, UK • +44 (0) 20 8896 1000

Rome, IT • Via Pieve Torina, 48, 00156 Rome, Italy • +39 (06) 32 111 683

Holzkirchen, DE • Ohmstrasse 3, 83607 Holzkirchen, Germany • +49 (80 24) 47 00-0

Hong Kong • Room 1801, 18/F, Tower 1 Phase 1, Enterprise Square, 9 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong • +852 2799 1220

Web • etconnect.com • Copyright©2017 ETC. All Rights Reserved. All product information and specifications subject to change. 4310L1002 Rev D 07/17