

# **Blizzard Lighting, LLC**

Phone: 1.866.493.6025 Fax: 1.866.870.0031 Email: info@blizzardlighting.com Website: http://www.blizzardlighting.com

# Amazing Wash, Beam, & Graphic Effects

Light up your performances with breathtaking beams and spectacular visual effects of the Stiletto™ I7!

Stiletto I7<sup>™</sup> comes fitted with 7\* ultra-bright OSRAM® 4-in-1 RGBW LEDs, and is jam packed with features. Its many talents include the ability to produce a narrow-to-wide zoomable wash, a sharp parallel beam, and then perform absolutely mind-blowing multibeam visual effects with its 4°- 60° beam angle. Add in infinite bidirectional lens rotation plus 540/270° pan/tilt to the mix to create a ton of motion and spectacular aerial effects.

Its 5-button LCD control panel allows you to set the fixture to automatically run in your choice of 3 auto modes, 2 sound active modes, or set it be controlled via 22/55-channel DMX to gain full control of every aspect including zoom, lens rotation, strobe, pan/ tilt, color macros, effect shape selection, speed, fade, color, shape offset between multiple fixtures, plus dedicated shape effect foreground and background dimmers. DMX mode also allows quick access to linear CTO presets (2500k-8000K), 4 dimming curves, and each of the LEDs are individual controllable for pixel mapping in 55-channel DMX mode!

On the back side of Stiletto I7<sup>™</sup> fixtures you will find industry standard PowerCON<sup>®</sup> compatible input/output connections and 3-pin DMX In/Out jacks. Preparing the fixture for truss mounting is also a snap by attaching its included dual quarter-turn "Omega" quick connect type clamp brackets.

The "Ayes" have it. Get your I7's today!

And of course, it is backed by Blizzard's 2-year warranty.

## Main Features:

- 7\* 15W ultra-bright OSRAM® 4-in-1 RGBW LEDs
- Pan: 540°/Tilt: 270° (8-16 Bit Resolution)
- Variable 4-60° beam angle
- Moving beam, wash, or kaleido effects
- Infinite bidirectional rotating lens
- Built-in auto and sound active programs
- Ultra-smooth 32-bit dimming
- Internal fan cooling system
- Easy-to-use 5-button LCD control panel
- PowerCON® compatible power in/out connectors
- Compact, high quality housing

#### Warranty:

• 2-year limited warranty, does not cover malfunction caused by damage to LEDs.





#### Power:

- 100-240VAC, 50-60 Hertz
- Power Consumption: 152W, 1.92A, PF: .65

#### Optical:

- Light Source: 7x15W OSRAM RGBW 4-in-1 LEDs
- Beam Angle: 4°- 60°
- Luminous Intensity: 31,869 Lux @ 2m (narrow), 1,587 Lux @ 2m (wide), 3,404 Lux @ 5m (narrow)
  - @ 2111 (WIGC), 3,404 EC

## Control:

- Protocol: USITT DMX-512
- 27/55-channel DMX Modes
- Standalone, Master/Slave, Auto, Sound Active
- 3-pin XLR In/Out Connections
- 5-button LCD control panel

#### Weight & Dimensions:

- 11.8" (300 mm) x 8.3" (210 mm) x 15" (380 mm)
- Weight: 9.3 lbs. (4.2 kg)