


LCD-1700V



The Biggest Thing in Big LCD Monitors



HM-400
Under-cabinet bracket



WM-300
Wall Mount Bracket



Side View

Active Matrix 17" Color LCD Monitor

- Hot key allows toggeling between video, S-Video, component, PC modes
- **PIP: Picture in picture capability**
- On-screen display for: brightness, contrast, back light, hue, volume
- Slim space saving design
- Composite, S-Video, component, and PC capability
- For color and B&W applications
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand included
- Built-in interface for wall or arm mounting
- VESA 100mm FPMPMI compliant
- Response Time: 35/20ms (rising/falling)

Optional Accessories

DC-1500	Factory approved car cord
HM-400	Hinge mount bracket (shown above)
WM-30	Wall mount bracket (fixed)
WM-300	Wall mount with swing arm & 4-way (shown above)
WM-1700V	Wall mount bracket (4-way adjustable)

Touch Screen: order LCD-1700TS

Display: 17.0" TFT LCD active matrix
 Back Light: Built-in (CCFT)
 Input Signal: Composite NTSC/PAL (auto switching), S-Video, Analog RGB

Resolution: SXGA 1280(H) x 1024(V) dots
 PC compatibility: IBM / MAC compatible
 Dot Pitch: 0.264(H) x 0.264(V)mm
 Brightness rating: 350 cd/m² (Nit)

Colors: 16.7M
 Contrast Ratio: 300:1
 Number of Pixels: 1,310,720 dots
 Viewing angle L/R/T/B: 70/70/40/70 degrees
 Pixel Configuration: Stripe

Input Signal Level: 1.0V P-P (positive) 75 Ohm
 Speakers: 8 ohms, 2W, 28 x 40mm oval type x 2
 Stereo Amplifier: 2 W x 2 @ 10% THD, 100 mV

Dimensions w/o desk stand (WHD): 426 x 376 x 67mm / 16.8" x 14.8" x 2.6"
 Dimensions w/ desk stand (WHD): 426 x 432 x 162mm / 16.8" x 17" x 6.4"

Actual visible screen size (WH): 338 x 270 mm / 13.3" x 10.6"
 Operating temperature: 50~104°F or 10~40°C

Power Requirement: Regulated 12VDC, 4A, negative ground

Part No. DC-1500 required for use in vehicles

Power Consumption: 45 W (max), 3 W (power saving off mode)

Includes switching power supply: 100 ~ 240VAC (auto-sensing), 50 ~ 60Hz, 1.2A

Rear Terminal Connections: BNC video IN/OUT jacks, 3.5 stereo audio OUT jacks, RCA video IN, RCA L/R audio IN
 2.1mm DC IN jack, S-Video jack
 15 pin mini D-sub (female)
 9-pin component IN

Net Weight: 7.3 kg./ 16 lbs.
 Gross Weight: 9.5 kg. / 21 lbs.

1319 Dexter Ave. N. • Ste. 020 • Seattle, WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

http://www.totevision.com



Schedule

GS-07F-0069L, SIN: 246-42(1), 246-50

Specifications subject to change without notice

© 2005 ToteVision

50K

Available through: