



# grandMA3 compact XT

Art.No. 4010505



The grandMA3 compact XT console is the larger of the two compact models, offering the full system benefits of the grandMA3 system, housed in a compact and lightweight format. Easy to transport, the compact models are ideal for owner/operators and also the console of choice for tech-desk duties.

The compact XT console features 2 huge multi-touch monitors, 5 dual encoders and a complete command section almost identical to the larger models.

With 60 physical playbacks, 16 assignable x-keys and a dedicated master playback section the grandMA3 compact XT console provides plenty of playback options.

The grandMA3 compact XT console includes 4,096 control parameters as standard, making it an ideal choice for small and medium sized professional entertainment lighting applications. The system size is scalable to 250,000 parameters with the use of additional grandMA3 processing units.

The grandMA3 compact XT is compatible with grandMA2 and grandMA3 software.

The grandMA3 lighting control consoles offer a fresh user interface with an optimized command section for intuitive and fast access.

The grandMA3 consoles features dual encoders, which provide users with intuitive control of additional features and functions. Feature-mapping of the dual encoders is customizable, facilitating ease of use and faster programming.

Long-life motorized playback faders are used across the entire grandMA3 console range. The faders incorporate a color-changing light pipe. All playbacks have direct access to button pushes as well as intensity and timing changes thanks to the new rotary RGB backlit encoders.



The grandMA3 operating system is completely new and has been designed to feel more welcoming to fresh converts without alienating existing grandMA programmers. Extensive user feedback has been incorporated to ensure the new functionality address' the real world needs of the MA family.

The fundamental syntax of the grandMA2 has been preserved and extended to facilitate the new functionality.

The grandMA3 software has an elegant new system-architecture incorporating new fixture, feature and effects-handling at it's very heart. These ground-breaking concepts from top industry visionaries, are presented within a refined user interface, and are designed to make practical tasks more intuitive. Selecting fixtures, adjusting values, storing presets and playing back cues should all feel familiar, but improved in many details of the process.

Better overview, faster access and more accurate information will create an improved user experience in programming and busking a show.

Fixture information is now generic and allows simpler sharing of programmed data between fixtures. We also support the new GDTF (General Device Type Format) natively, allowing fixture manufactures to ensure their own fixtures are controlled as intended.

For more details of the current software version see the software category in the product section.

## Features

- Real-time control for up to 250,000 parameters per session in connection with grandMA3 processing units
- 6 DMX outputs, 1 DMX input
- 2 internal foldable monitor multi-touch screens
- 1 external multi-touch screen can be connected
- 39 rotary RGB backlit encoder
- 5 dual encoders
- 15 backlit motorized 60mm faders
- 60 separate playbacks
- 16 assignable x-keys
- 3 etherCON connectors, 5 USB connectors
- 2 backlit motorized A/B faders 100mm
- Individually backlit and dimmable silent (clickless) keys

## Scope of delivery

| Art.No. | Article  | Qty. |
|---------|--|------|
| 4011453 | Dust cover grandMA3 compact XT   | 1    |
| 4011080 | MA LED desk lamp grandMA3, straight plug XLR 4pin, length 27", incl. cover | 1    |
| 4011386 | MA Magnetic plate for easy labeling of 15 faders, for grandMA3             | 1    |

### Additional scope of delivery

1x powerCON TRUE1 connector (NAC3FX-W)



## Technical Specifications

|  |   |
|--|---|
| <b>Operating voltage/ Supply voltage</b> | 100-240V, 50/60Hz   |
| <b>Net weight</b>                        | 20 kg / 45 lbs  |
| <b>Power</b>                             | max. 250VA  |
| <b>Dimensions</b>                        | 845 x 429 x 160 mm / 34 x 17 x 7 in<br>(width x depth x height, folded)   |
|  | 845 x 563 x 325 (max. 410) mm / 34 x 23 x 13 (max. 17) in<br>(width x depth x height, unfolded)   |
| <b>Parameters Mode2</b>                  | 4,096 (HTP/LTP)   |
| <b>Parameters</b>                        | 4,096 (HTP/LTP)   |
| <b>Connectors</b>                        | 1 x powerCON TRUE1<br>3 x etherCON/RJ45<br>6 x DMX512-A Out (5pin XLR female)<br>1 x DMX512-A In (5pin XLR male)<br>1 x MIDI In (5pin DIN female)<br>1 x MIDI Out (5pin DIN female)<br>1 x Linear Timecode In (3pin XLR female)<br>1 x Audio In (3pin XLR female)<br>1 x GPI General Purpose Interface (D-SUB DE9 female) for remote control<br>1 x DisplayPort 1.2 for external screens<br>2 x S/PDIF In and Out<br>3 x USB 2.0 (type A)<br>2 x USB 3.0 (type A)<br>1 x LED desk light (4pin XLR female) |

## Article

| Art.No. | Article             |
|---------|---------------------|
| 4010505 | grandMA3 compact XT |

## Accessories

| Art.No. | Article                     |
|---------|-----------------------------|
| 4011674 | MA Case grandMA3 compact XT |



More product pictures

