

Remote Power Packs

PPA Series

The **PPA-1** rechargeable gel-cell pack powers a mixer for approximately six hours and can be recharged overnight with the included dual-mode charger.

The **PPA-1** is capable of approximately 500 charge-discharge cycles. Integrated power pack assembly for remote operation, which mounts to a mixer. Includes housing with rechargeable 24VDC gel-cell battery pack (four to six hours operation), and an external battery charger operating at 115VAC/60 Hz.

The **PPA-2** operates the same as above except battery charger operating at 230VAC/50 Hz. Euro-plug. Contact factory for other plug configurations. The **PPA-B** supplies an extra 24VDC rechargeable gel-cell battery pack, charger not included.

The **PPA-1**, **PPA-2**, and the **PPA-B** can all mount directly to the underside of the NANOAMP case or slips into the quick-change slide mounts provided with the PROK-1 protection kit or the ABAG-1 carrying case. A NP-1 type battery and a spare can be Velcro to the inside of the carry case.

Image
Coming
Soon

Models

- **PPA-1** - 24VDC Rechargeable Battery Pack with dual mode fast charger and an external battery charger operating at 115VAC/60 Hz.
- **PPA-2** - 24VDC Rechargeable Battery Pack with dual mode fast charger and an external battery charger operating at 230VAC/50 Hz.
- **PPA-B** - 24VDC Rechargeable Battery Pack with dual mode fast charger and an external battery charger operating at an extra 24VDC.

Remote Power Packs

Technical Specifications

PPA Series

BATTERY LIFE	Rechargeable 24VDC gel-cell battery pack for four to six hours operation.
PPA-1:	An external battery charger operating at 115VAC/60 Hz.
PPA-2:	230VAC/50 Hz and Euro-plug.
PPA-B:	Extra 24VDC rechargeable gel-cell battery pack, charger not included.
COMPATIBILITY	Functional with: MX100 MX100C MX101 XP100 MX200 MX200C MXS100 XPS100 XPS200
WARRANTY	Limited, One Year Warranty