

# **SL-4.1**R

## DESCRIPTION

The **SL-4.1R** is an slim 2-way loudspeaker designed to be surface-mounted and disappear into the architectural surroundings. Its precision ribbon HF driver and four 4" longexcursion LF drivers renders complex audio program with detail and clarity that does not seem possible from such a small package.

The addition of an available SBC-210 ceiling mounted sub-woofer extends low frequency response to 34 Hz and increases maximum system SPL.

#### **KEY FEATURES:**

- slim profile (only 2" deep by 4" wide)
- 120° H x 90° V coverage
- employs precision ribbon HF driver
- blends into architectural environment
- easily integrated into architectural casework with optional millwork adapter kit

#### **APPLICATIONS:**

- sound for video presentation
- premium home theater LCR
- premium home theater surrounds
- delay fill
- theatrical effects

#### NOMINAL DATA

Frequency Response	$120-20{,}000 \ Hz \ \pm 3 \ dB$
Sensitivity	92 dB @ 2.83 volts / 1M
Impedance	8Ω
Power Handling	150 W long term program
Maximum Output	111 dB long term / 117 dB peak @ 1 meter
Nominal Coverage Angles	120° H x 90° V
Dimensions	height: 30.50 " / 775 mm width: 4.56 " / 116 mm depth: 2.06 " / 52 mm
Net Weight	11.0 lbs / 5.0 kg
Shipping Weight	13.9 lbs / 6.3 kg



### DESCRIPTIVE DATA

System Configuration	Low profile 2-way
Components & Loading	<ul><li>(4) 4 " long-excursion LF drivers;</li><li>(1) 3" ribbon HF driver</li></ul>
High-Pass Filter	Built-in 1 <sup>st</sup> order @ 120 Hz
Enclosure Type	Sealed enclosure, very low profile
Enclosure Material	Steel chassis, with composite endcaps
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	Mounting brackets included
Grille	Integral, fabric wrapped

296 North Pascal Street Saint Paul MN 55104

## innovoxaudio.com PROUDLY MADE IN THE U.S.A.