

Colored LED Strobe / Cyc Light

Cyc Out™ retains all the charm of a classic white strobe with the additional benefit of RGBW color mixing for colored strobe effects, blinder effects, or wide/even wash effects with continuous bright colored light output, all without the need of gels.

The fixture has a light source of 256 x (64* R/G/B/W) 3W LEDs, a 60° beam angle, and just like classic strobe fixtures, the light is projected forward and enhanced by a parabolic reflector (rather than directly forward like most LED strobes.) The beam angle can also be shaped using its equipped 2 leaf barn doors.

The strobe rate, intensity, and duration of the pulse are all fully controllable in both standalone and DMX modes. There are 3 DMX channel modes: 9-channel allows RGBW color mixing, 15-channel is color mixing + strobe, and 27-channel is color mixing + strobe, and the added ability of independent (top/bottom) zone control.

It also offers flicker-free LEDs, an automated fan cooling system, 32-bit dimming, and a mounting bracket with stabilizers for free standing position flexibility.

And on the back of the fixture you'll find an easy-to-use control panel with a Micro OLED display with 4* touch sensitive buttons, power switch, 3/5-pin XLR in/out connections, and a powerCON™ compatible AC power input connector.

And of course, it is backed by Blizzard's 2-year warranty.

Main Features:

- 256 x (64* R/G/B/W) 3W LEDs, 50,000-100,000 hours
- Dual zone control (top/bottom) in 27ch DMX mode
- Individual R/G/B/W intensity, strobe duration, and rate control
- Wide 60° beam angle, plus 2 leaf barn door set
- User-selectable 32-bit dimming curves
- Variable electronic dimming & strobe
- Automated temperature controlled, or continual fan cooling
- Static color mixing in standalone mode
- Flicker-free constant-current 1500HZ LED driver
- Micro OLED display menu with 4* touch sensitive buttons
- Mounting bracket w/stabilizers for free standing positioning
- 9/15/27-channel DMX modes
- 3/5-pin male input and 3/5-pin female output
- PowerCON™ compatible AC power input connector

Warranty:

- 2-year limited warranty, does not cover malfunction caused by damage to LEDs.

CYC OUT™



Power:

- 100-264VAC, 47-63 Hertz
- Power Consumption: 663W, 5.8A, PF: .99

Optical:

- Light Source: 256 x (64* R/G/B/W) 3W LEDs
- Beam Angle: 60°
- Luminous Intensity: 2,076 Lux @ 2m | 376 Lux @ 5m

Control:

- Protocol: USITT DMX-512
- 9/15/27-channel DMX modes
- Standalone, master/slave mode
- 3/5-pin XLR In/Out connections
- 4-button control panel w/Micro OLED display

Weight & Dimensions:

- 17.8" (452.5 mm) x 6" (151.8 mm) x 10" (255 mm)
- Weight: 16.3 lbs. (7.4 kg)