

The E 865 represents the first condenser microphone in the acclaimed Evolution Series. A live performance, lead vocal microphone, the E 865 easily cuts through high on-stage levels by virtue of its detailed and natural 40 Hz - 20 kHz reproduction and superb transient response. Its smooth super-cardioid polar pattern rejects feedback with low, off-axis coloration. The E 865 withstands sound pressure levels of up to 150 dB, and deftly suppresses pop noise. While it picks up the finest sonic nuances, the E 865 is at the same time rugged, benefiting from high-quality workmanship and a robust all-metal housing. The microphone ships with a pouch and mic clip.

Features

- Steel inlet basket
- Superb transient response
- Handles high levels of sound
- Rugged, robust all-metal housing
- One-year warranty



Technical Data

Transducer	Electret condenser
Frequency response	40 - 20,000 Hz
Pick-up pattern	Super-cardioid
Maximum SPL	150 dB
Sensitivity (free field, no load) 1kHz	3 mV/Pa
Nominal impedance at 1 kHz	200 Ω
Min. terminating impedance	1k Ω
Power supply	12V - 48V phantom powering
Weight (without cable)	approx. 11 oz.
Dimensions	\varnothing =1.9 in., L=7.72 in.

Delivery Includes

1 E 865, 1 pouch, 1 MZQ 800 mic clip