



---

**For Accurate Music and  
Voice Reproduction from  
In-Ceiling Locations**

---



**6-1/2" IN-CEILING LOUDSPEAKER**

**LSC-6**

# LSC-6

## 6-1/2" IN-CEILING LOUDSPEAKER



### FEATURES

- 6-1/2" talc-filled polypropylene woofer with treated foam rubber surround
- 3/4" pivoting liquid cooled polycarbonate dome tweeter
- Moisture and UV resistant
- Rust proof aluminum grilles

### INSTALLATION FRIENDLY DESIGN:

- Suitable for painting
- Connection terminals accept up to 12 gauge speaker wire
- Quick mounting system for new construction or retrofit installations
- Includes hole template and paint mask
- Ceiling Bracket for new construction: JobSite NCB-6 (sold separately)

### SPECIFICATIONS

- Power handling: 5 – 75 watts
- Frequency response 65Hz-20kHz +/- 3dB
- Impedance: 6 ohms

### DIMENSIONS

- 9-1/4" outside diameter
- 8" diameter hole cutout
- 3-1/2" deep when installed in 1/2" drywall

### WARRANTY

- Warranty: 5 year limited

#### JOBSITE SYSTEMS

12331 SW 130 STREET  
MIAMI, FL 33186

**P** 866.4JB.SITE (866.452.7483)

**F** 305.238.0185

[WWW.JOBSITESYSTEMS.COM](http://WWW.JOBSITESYSTEMS.COM)

©2004 Niles Audio Corporation. JobSite, Pure Custom and Niles are registered trademarks of Niles Audio Corporation and the JobSite Logo is a trademark of Niles Audio Corporation. JSLSC6PDF

Specifications subject to change without notice.