

WXY4000 XY STEREO HOLDER FOR DPA WINDPAC



www.dpamicrophones.com

DPA 
MICROPHONES

WXY4000 XY STEREO HOLDER FOR DPA WINDPAC

WXY4000 is an XY Stereo Holder for use with the DPA WINDPAC windshield system to create the ideal tool for location recording in stereo.

Two DPA 4023 Compact Cardioid microphones are mounted in the WXY4000 to form a coincident intensity difference XY stereo configuration with 90° between the capsules. This provides a compact stereo microphone for XY stereo recording in ENG/EFP applications. The integral windshield and shock mount system makes the setup particularly suitable for location recording.

The WXY4000 is constructed from black anodized aluminium with rubber mounting rings to ensure durability and stability. It has two LEMO connectors for simple and safe mounting and removal of the microphones. The audio signal is routed directly to the 5-pin XLR male stereo output connector via a phantom adapter circuit.

The WXY4000 can also be used with the DPA UA0897 Shock Mount for applications ranging from stand mounting in the studio through to close miking of instruments such as piano.

Specifications:

Power Supply:
48 V Phantom

Connector:
5-pin XLR

Weight:
58 g (2 oz)

Length:
159 mm (6.3 in)

Diameter:
19 mm (0.7 in)



DPA 
MICROPHONES

DPA Microphones A/S
Gydevang 42-44
DK-3450 Allerød, Denmark
Ph: +45 4814 2828
Fax: +45 4814 2700
info@dpamicrophones.com
www.dpamicrophones.com