NANLITE

LumiPad	NanLite LumiPad 11 Dimmable Adjustable Bicolor Slim Soft Light AC/Battery Powered LED Panel	NanLite LumiPad 25 High Output Dimmable Adjustable Bicolor Slim Soft Light AC/Battery Powered LED Panel
Product Weight (lb)	0.6	2.2
Product Length (in)	6.5	13.6
Product Width (in)	1.4	2.2
Product Height (in)	4.5	12.2
Color Temp (Kelvin)	3200К-5600К	3200K-5600K
CRI	95	95
TLCI	93	93
Lux @ 1m 3200K	320	867
Lux @ 2m 3200K	76	216
Lux @ 3m 3200K	36	97
Lux @ 1m 5600K	337	930
Lux @ 2m 5600K	75	232
Lux @ 3m 5600K	39	104
Lumen Output 3200K	969	2140
Lumen Output 5600K	969	2140
Dimming	0-100%	0-100%
Cooling System	Passive	Passive
Max Power Consumption	11.5w	25w
Power Source	7.2-15V DC	15-24V DC
Compatible D-Tap Adapter	NanLite CB-DT-DC D-Tap cable with DC Socket	NanLite CB-DT-DC D-Tap cable with DC Socket
Battery Compatibility	Sony NP-F550 / F750 / F970 series (Not Included)	Sony NP-F550 / F750 / F970 series (Not Included)
Charger	Not Included	Not Included
Charge Time to Full (Hours)	Battery Dependent	Battery Dependent
Charge Time to 80% (Hours)	Battery Dependent	Battery Dependent
Runtime @ 10% Brightness (Hours)	1 x NP-F550: 13 hours 1 x NP-F750: 28 hours 1 x NP-F970: 37 hours	1 × NP-F550: 7 hours 1 × NP-F750: 13 hours 1 × NP-F970: 17 hours
Runtime <i>@</i> 50% Brightness (Hours)	1 × NP-F550: 3 hours 1 × NP-F750: 6 hours 1 × NP-F970: 7 hours	1 x NP-F550: 1 hours 1 x NP-F750: 3 hours 1 x NP-F970: 3 hours
Runtime <i>@</i> 100% Brightness (Hours)	1 x NP-F550: 1.4hours 1 x NP-F750: 2.8hours 1 x NP-F970: 3.7hours	1 x NP-F550: 0.7 hours 1 x NP-F750: 1.3 hours 1 x NP-F970: 1.7 hours
DMX Control	No	No
Wireless Control Type	Wireless Remote / Wifi via adapter	None
Compatible Remote	NanLite RC-1 Remote Control	N/A
Frequency	2.4ghz	N/A
Compatible Wifi Adapter	NanLite W-2 Wifi Adapter	N/A
Mount	1/4 20" and Cold Shoe	5/8" Receiver
Warranty	Limited 2 Year Warranty (extend to 3 years total <u>here</u>)	Limited 2 Year Warranty (extend to 3 years total <u>here</u>)