Isobar Surge Suppressor

Premium surge, spike and line noise protection



Model #: ISOBAR6ULTRA

- 6 outlets/6-ft. cord
- 2350 joule rating
- All metal housing with LEDs
- Isolated filter banks
- \$50,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

DESCRIPTION

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar Premium surge and noise suppressors to protect sensitive computer, networking and telecom equipment. With more than 14 million satisfied customers, the Isobar remains the world's number one selling premium surge suppressor. Loaded with a generous combination of high quality components, near indestructible all-metal case and unique noise filtration system, the Isobar offers the highest level of protection attainable in a multi-outlet strip. Robust surge suppression circuits with sine-wave tracking offer extreme levels of protection against the heaviest surge conditions exceeding IEEE 587 category A & B specifications and reducing 6,000V test surges to harmless levels under 35 volts. Isobar's unique protection system combines large torroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference, even noise generated by other pieces of connected equipment. ISOBAR6ULTRA offers 6 outlets arranged in three filter banks to prevent system crashes, reboots and performance problems common as noisy system peripherals are powered off and on. Surge suppression rated at 2350 joules / 97,000 amps offers network-grade protection. Widely spaced NEMA 5-15 outlets accommodate up to 4 large transformer plugs without blocking outlets. Diagnostic LEDs confirm power availability, line fault and protection status. Includes 6 foot AC line cord with space-saving angled input plug, keyhole mounting tabs and a set of 4 child safety covers. Lifetime warranty with \$50,000 Ultimate Lifetime connected equipment Insurance (USA & Canada Only).

PLUG / OUTLETS: Input: NEMA 5-15P / Output: 6 NEMA5-15R / 6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping / 2350 joules / 97,000 amps

FORMAT: Corded all-metal strip with transformer spaced outlets

KEY BUYING POINTS

- Tripp Lite's ISOBAR is the world's number one selling premium suppressor series with more than 14 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine-wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B
 specifications and reducing 6,000V test surges to harmless levels less than 35 volts.
- Multi-component suppression circuits combine torroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of
 metal oxide varistors into exclusive isolated filter banks that remove EMI/RFI interference, even noise from other pieces of connected
 equipment.
- 6 outlets arranged in three filter banks prevent system crashes, reboots and performance problems common as noisy peripherals are powered off and on.
- Network grade surge suppression rated at 2350 joules / 97,000 amps
- · Widely spaced outlets accommodate up to 4 large transformer plugs without blocking outlets
- 3 LED indicators confirm suppressor operation and site wiring status, plus warning of suppressor or electrical fault conditions
- Lighted power switch confirms power on/off status
- 6 foot AC line cord with space-saving angled input plug 6 foot AC line cord with space-saving angled input plug
- Keyhole mounting tabs allow permanent installation
- Set of 4 outlet covers safely seal off unused outlets
- 120VAC, 50/60Hz electrical compatibility

- \$50,000 Ultimate Lifetime Insurance (USA & Canada Only)
- Lifetime product warranty
- UL1449 listed surge suppression (330V let-through), UL1283 listed EMI protection, UL1363 listed power tap, cUL approved to Canadian standards

TYPICAL APPLICATIONS

Ideal for premium protection of personal computers with peripherals, network and CAD / CAM / CAE workstations, internetworking
accessories, telecommunications systems, point of sale equipment, audio / video and home theater systems in any home, office or
industrial application.

PACKAGE INCLUDES

- ISOBAR6ULTRA premium surge suppressor
- RJ11 telephone cable
- Set of 4 outlet safety covers
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview: ISOBAR ULTRA premium surge and noise suppression system prevents equipment damage

and performance problems resulting from damaging transient surges and line noise. Active filter network maintains noise-free output with zero reaction / response time. Rugged all-metal, mountable housing fitted with high quality duplex style output receptacles. 6 outlets, 2350 joules AC protection level, less than 35V let through voltage, 3 diagnostic LEDs.

Voltage compatibility: 120 VAC
Frequency compatibility: 50/60 Hz

OUTPUT

Output volt amp capacity (amps): 12
Output watt capacity (watts): 1440

Outlet quantity / type: 6 NEMA 5-15R

Transformer accommodation: Supports up to 4 large transformer plug accessories without covering remaining outlets

INPUT

Input connection type: NEMA 5-15P input plug

Input cord length (ft.): 6 ft.
Input cord length (m): 1.8

Recommended electrical service: 120V,15A

LEDS ALARMS & SWITCHES

Diagnostic LEDs: PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)

Switches: Two position red illuminated on/off power switch

AC SURGE / NOISE SUPPRESSION

Protection modes: Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression

AC suppression joule rating: 2350 joules

Clamping voltage (RMS): 140V

AC suppression response time: NM = 0 ns. CM = <1 ns

AC suppression surge current rating: 97,000 amps (36,000 NM / 61,000 CM)

AC suppression components used: Metal oxide varistors, toroidal balanced chokes, ferrite rod-core inductors and VHF

capacitors.

Safe thermal fusing: Prevents unsafe conditions during extreme extended overvoltages and catastrophic

occurences

UL1499 let through rating: 330V - UL Verified

IEEE587 Cat. A ringwave let through: Less than 35 volts

EMI / RFI filtering: 40-80 dB

Isolated filter banks:Unique isolated filter bank design offers additional filtering between each duplex pair of

outlets on the strip to prevent electrical noise interference between connected loads. Includes

3 filter banks.

Immunity: Conforms to IEE 587 / ANSI C62.41

PHYSICAL

Unit Dimensions (HWD/in): $2.5 \times 7 \times 3.5$ Unit Dimensions (HWD/cm): $6.4 \times 17.8 \times 8.9$

Material of construction: Metal

Integrated keyhole mounting tabs: Metal end caps are fitted with keyhole mounting tabs for wallmount installation

Housing color: Gray

Receptacle color: Black

AC line cord color: Gray

CERTIFICATIONS

 UL1449 1998 Rev. (AC Suppression):
 UL1449

 UL1283 (EMI Filter):
 UL1283

 UL1363 (Power Tap):
 UL1363

 cUL / CSA (Canada):
 cUL

Approvals: Exceeds IEEE 587 category A&B specifications

WARRANTY

Product warranty: Lifetime

Connected equipment insurance (USA and \$50,000

Canada Only):

SPECIAL FEATURES

Appearance: Rugged all-metal corded strip format with high quality duplex receptacles

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.