



## LED-2154HDSDI

This high performance LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness which is ideal for professional broadcast production and HD-SDI video surveillance.

### Benefits

- LED backlight: brighter picture using less power
- Full HD (1080i/p) with no downscaling
- Great picture quality with motion adaptive 3D De-Interlacer, digital noise reduction and 4H Comb filter Y/C separation
- HD-SDI Input and Output (Loop-through)
- Durable metal case
- Removable deskstand

### Specifications

<b>Mount</b>	VESA 100 x 100mm; Removable Deskstand
<b>HD Compatible</b>	Yes
<b>Anti Glare Coating</b>	Yes
<b>Case</b>	Durable Metal
<b>IR Remote Control</b>	Yes
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	18.76" x 10.5" / 476.6 x 268.1mm
<b>Resolution</b>	1920 x 1080 (Full HD)
<b>Brightness Rating</b>	250 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED (50K)
<b>Dot Pitch</b>	0.24825(H) x 0.24825(V)mm
<b>Color Depth</b>	16.7M
<b>Number of Pixels</b>	2,073,600
<b>Response Time</b>	3.8ms/1.2ms (Rising/Falling)
<b>Audio Power / Speakers</b>	2 Speakers x 1.5 Watts
<b>Viewing Angle (L/R/T/B)</b>	85/85/80/80 degrees
<b>3D Comb Filter</b>	Yes
<b>Dimensions w/ Deskstand</b>	20.1" x 12.2" x 2.8" / 510 x 310 x 70mm
<b>Dimensions</b>	20.1" x 12.2" x 2.4" / 510 x 310 x 60mm
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Humidity</b>	10% ~ 90%
<b>Power Requirements</b>	100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included
<b>Power Consumption</b>	30 Watts (Active); < 3 Watts (Stand-by)
<b>3GSDI</b>	x1 HD-SDI Input; x1 HD-SDI Output
<b>HDMI</b>	x1 Input
<b>Audio</b>	x1 RCA L/R Input; x1 PC Input
<b>Power</b>	x1 2.5mm DC Input
<b>Weight</b>	Net: 12.95 lbs / 5.9 kg

Specifications subject to change.