

# Technical Data Sheet

## Plenum Communication Cables

# WEST PENN WIRE

2833 West Chestnut Street  
Washington, PA 15301  
Toll Free: (800) 245-4964  
Fax: (724) 222-6420  
www.westpenn-wpw.com



<b>PART NUMBER:</b>	<b>25290B</b>
<b>DESCRIPTION:</b>	22/2 Solid bare copper conductors, shielded with an overall jacket.
<b>NEC RATING:</b>	CMP, NEC Article 800
<b>APPROVALS:</b>	(UL) C(UL) Listed or c(ETL)us Listed
<b>APPLICATION:</b>	Indoor within ducts, plenums, and other spaces used for environmental air for (Intercom Systems, Security Systems, Sound, Audio, Background Music)

### Construction Parameters:

Conductor	22 AWG Bare Copper
Stranding	Solid
Insulation Material	Polymer Alloy
Insulation Thickness	0.010" Nom.
Number of Conductors	2
Shield	100% Aluminum Polyester Foil
Drain	Stranded Tinned Copper
Jacket Material	Flexible Plenum
Jacket Thickness	0.015" Nom.
Overall Cable Diameter	0.121" Nom.
Approximate Cable Weight	11 Lbs/1M' Nom.
Flame Rating	NFPA 262 Flame Test

### Electrical & Environmental Properties:

Temperature Rating	-10°C To +60°C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	54 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	97 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	17.5 Ohms/1M' Nom.
Insulation Colors	Black, Red
Jacket Color	Gray
RoHS Compliant	--

### Mechanical Properties:

Max. Recommended Pull Tension	28 lbs
Min. Bend Radius (Install)	1.25"

Specification Issue Date: 7/06

This document is the property of West Penn Wire.  
The information contained herein is considered  
Proprietary and not to be reproduced by any means  
Without written consent of West Penn Wire

**Cold Environment Precautions:** Due to the nature of  
PVC Compounds to become non-pliable when stored  
or handled in ambient temperatures of 32 deg. F or  
less, we recommend the following:

**“Prior to installation, condition the cable for at  
least 24 hours at room temperature to provide the  
best flex properties for ease of installation.”**

Standard Lengths are 1000ft.  
The Jacket is sequentially footmarked.  
The information presented here is, to the best of our  
knowledge, is true and accurate. However, since  
conditions of use are beyond our control, all  
recommendations or suggestions are presented  
without guarantee or responsibility on our part. We  
disclaim all liability in connection with the use of  
information contained herein or otherwise.