

CHAMELEON MICRO SPOT PM GALAXY AUDIO

ULTRA
COMPACT
LOUDSPEAKER

CHAMELEON SERIES MSPM

The Chameleon Micro Spot, originally designed for courtroom applications, is ideal for fixed installation applications such as paging systems, boardrooms, etc. Standard features of the Chameleon Micro Spot include a universal wall/ceiling bracket and a 70volt transformer with 6 adjustable taps of .9w, 1.8w, 3.7w, 7.5w, 15w, 30w, and a 16 ohm position. The 16 ohm position is a transformer bypass that allows the user to step around the transformer and use the Chameleon Micro Spot as a 100 watt speaker. The bracket allows the Chameleon Micro Spot to be mounted to any wall, ceiling, table, or other surface. The Chameleon Micro Spot features the proprietary Galaxy Audio NEOLITE neodymium 5-inch driver with a Ferrofluid cooled voice coil that reduces both power compression and distortion.



MSPM-B



MSPM-W

CHAMELEON MICRO SPOT PM GALAXY AUDIO

ULTRA COMPACT LOUDSPEAKER

SPECIFICATIONS

Frequency response: 150 Hz –18 kHz

Power handling capacity: 100 Watts

Sensitivity: (1 watt @ 1Meter) 92 dB (1 kHz octave band)

Maximum SPL: (100 watts @ .5 meter): 117 dB

Splowt: 43*

Speaker complement: One NEOLITE Neodymium, ferrofluid cooled 5-inch driver .86 lbs (.39 kg)

Nominal impedance: 16 ohms

Input connection: Push terminals

Enclosure Materials: High impact ABS and Styrene plastic

Color: Black case with cloth covered ABS grille

Tap Selector: 6 taps plus a 16 ohm position; .9w, 1.8w, 3.7w, 7.5w, 15w, 30w, and 16 ohms

Dimensions: 7-inches x 6-inches x 5.125-inches (178 mm x 152 mm x 130 mm)

Net weight: 3.68 lbs. (1.669 kg) (without bracket)

Shipping weight: 5.62 lbs. (2.55 kg)

* **Splowt** A unit of measure, expressed as dB, that divides a speaker's maximum SPL by its weight in pounds.

MSPM-B

Black CHAMELEON

MSPM-W

White CHAMELEON



FerroSound
The Solution Is Loud And Clear™

ARCHITECT AND ENGINEER SPECIFICATIONS

The loudspeaker shall be a controlled bandwidth system offering one NEODYMIUM ferrofluid cooled 5-inch driver. The loudspeaker shall be capable of handling 100 watts of continuous program. Nominal impedance shall be 16 ohms. A 70 volt transformer with 6 adjustable taps of .9w, 1.8w, 3.7w, 7.5w, 15w, 30w, and a direct 16 ohm bypass shall be included. Input connections shall be push terminals. The enclosure shall be constructed of rugged ABS and Styrene plastic and feature a cloth covered ABS grille. The cabinet shall be available in black or white. A bracket shall be included to allow the unit to be secured to a wall or ceiling. Dimensions shall be 6.0 inches wide (152 mm), 7 inches high (178 mm), and 5.125 inches deep (130 mm). The system weight shall be 3.68 lbs (1.669 kg). The loudspeaker system shall be the Galaxy Audio CHAMELEON MICRO SPOT.

Specifications subject to change without notice.

GALAXY AUDIO

MAKERS OF THE ORIGINAL HOT SPOT PERSONAL MONITOR

601 E. Pawnee Wichita, KS 67211 316.263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed outside the United States by **E and E Exports, Inc.** 2815 Junipero Ave. Suite 101 Signal Hill, CA 92614

562.988.3447 FAX 562.989.3037

Distributed in Canada by **Audio Distributors International (ADI)** 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada

450.449.8177 FAX 450.449.8180