

EXPOSÉ

THE EXPOSÉ E8B REPRESENTS THE HEART & SOUL OF KRK ENGINEERING & DESIGN

The KRK Exposé line has long been the go to solution for close-field monitoring by the majority of the worlds most respected engineers and producers. The new E8B carries the legacy of KRK's Exposé line to new heights. The trademark yellow Kevlar woofer remains intact as do the distinctive radiused edges that quickly identify any KRK monitor both in sound and style. The radiused edges have been significantly increased resulting in much more natural diffraction and a HUGE sweet spot. The B in the E8B stands for Beryllium. The AlBeMET tweeter used on the E8B results in even greater transient response as well as high frequencies that go beyond the range of human hearing. All of the design elements are contained in a new, highly attractive and very rigid cabinet.



FEATURES & BENEFITS

- Uncompromised high-grade dual amplification system for incredible detail
- Aluminum/Beryllium composite (AlBeMET) inverted dome high frequency transducer provides smooth, lightning fast transient response
- Extended HF frequencies ideal for use with high sample rate computer audio systems
- Increased cabinet radius edges improve natural diffraction and provide a larger sweet spot
- Attractive new enclosure looks great in any recording environment

EXPOSÉ E8B SPECIFICATIONS

Shielded	Standard
Drivers	Tweeter: 1" AlBeMET Inverted Dome Woofer: 8" Dual Layer Kevlar w/Rohacell
Input Type	XLR (3-Pin) 10k Ohm Balanced Pin1 = Ground Pin2 = (+) High Pin3 = (-) Low
Controls	Input Sensitivity: +6dB HF SHELF: +1.0dB to -2.0dB in 0.5dB increments. Shelved @ 10Hz. 7-Position Switch HF ADJUST: +1.0dB to -2.0dB in 0.5dB increments. Shelved @ 1.9Hz. 7-Position Switch LF ADJUST: Whole Space (-3dB @40Hz), Half Space (-3dB @48Hz), Quarter Space (-3dB @62Hz). 3 Position Switch
Amplification	HF: 120Watts Discrete Class A/AB LF: 120Watts Discrete Class A/AB
Fusing	6.0A 100VAC 50Hz 6.0A 110-120VAC 50/60Hz 3.15A 220-240CVAC 50/60Hz
Max Power Consumption	500W
Freq. Response Crossover Point	40Hz - 30kHz +/-1dB
Max SPL (each)	Music: 112dB Peak: 115dB
Cabinet Dimensions	19.3" H x 14.6" W x 14" D / 491mm H x 370mm W x 355mm D
Shipping Carton	24.8" H x 18.2" W x 18.7" D / 630mm H x 463mm W x 476mm D
Cabinet Weight	67lbs / 30.40 Kg
Shipping Carton	75.6lbs / 34.31 Kg
Optional Benefits	Omni Mount 120.0 WBX Hardware is installed into the inserts to mount the 120.0 WBX Base



USA: 3000 SW 42 St. Hollywood, FL 33312 • Telephone 1.954.316.1580 • Fax 1.954.316.1590

Europe: 382 Avenue de la Couronne, 1050 Brussels, Belgium • Telephone +32 2 645 05 00 • Fax +32 2 645 05 05