

Technical Data Sheet

Communication Cables



2833 West Chestnut Street
Washington, PA 15301
Toll Free: (800) 245-4964
Fax: (724) 222-6420
www.westpenn-wpw.com

PART NUMBER:	C206
DESCRIPTION:	14/2 Stranded bare copper conductors, unshielded & unjacketed- Cluster Speaker Cable
NEC RATING:	CL2, NEC Article 725
APPROVALS:	(UL) or (ETL)us Listed
APPLICATION:	Indoor for: Cluster Speaker.

Construction Parameters:

Conductor	14 AWG Bare Copper
Stranding	41x30
Insulation Material	PVC/ Nylon
Insulation Thickness	0.015" PVC Nom. 0.005" Nylon Nom.
Number of Conductors	2
Shield	None
Drain	None
Jacket Material	None
Jacket Thickness	None
Overall Cable Diameter	0.222" Nom.
Approximate Cable Weight	34Lbs/1M' Nom.
Flame Rating	UL 1685

Electrical & Environmental Properties:

Temperature Rating	-20deg C to 60deg C
Operating Voltage	300 V RMS
Max.Capacitance Between Conductors @ 1 KHz	31 pf/ft Nom.
DC Resistance per Conductor @ 20deg C	2.7 Ohms/1M' Nom.
Insulation Colors	Black ,White
Jacket Color	None
RoHS Compliant	--

Mechanical Properties:

Max. Recommended Pull Tension	84 Lbs.
Min. Bend Radius (Install)	2.2"

Specification Issue Date: 7/06

This document is the property of West Penn Wire.
The information contained herein is considered
Proprietary and not to be reproduced by any means
Without written consent of West Penn Wire

Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our
knowledge, is true and accurate. However, since
conditions of use are beyond our control, all
recommendations or suggestions are presented
without guarantee or responsibility on our part. We
disclaim all liability in connection with the use of
information contained herein or otherwise.