# SPLITTERS/COMBINERS/DIRECT BOXES/ACCESSORIES

### ĂKĠ B18E Phantom Power Supply

HEADPHONES

MIXERS

CD PLAYERS

RECORDERS

SIGNAL PROCESSING

AMPLIFIERS

SPEAKERS

VIDEO

LIGHTING

STANDS

FURNITURE

CASES/BAGS

POWER

EQUIPMENT

TOOLS



Single channel battery operated phantom power supply. Requires two 9 volt batteries. Optional A48V adapter is available to convert to 48 volt phantom powering capability. B18E LIST 187.00 A48V

**CALL FOR PRICE** 



ply with internal regulated power supply with 6' grounded line cord. The AT8801 is a single channel 48V phantom supply which operates from a wall-wort module. LIST CP8506 .....180.00 

**CALL FOR PRICE** 



### $(\Lambda)$ audio technica. UniTools In-Line Mic Processors

UniTools are 24-48 volt phantom powered microphone accessories that pass the phantom power on to the mic. The rugged steel housings can be mounted anywhere in-line, either near the mixer or the mic. LIST

AT8681UniMix 2 to 1 mic combiner	
with balance control	70.00
AT8684 UniMute Switch operated	
57dB attenuator	70.00
CALL FOR PRICE	



The DI20 converts 2 -unbalanced 1/4" jack inputs into 2-balanced XLR outputs. There is a 2-channel/link mode for flexible usage as mono, 2-channel or splitter box. Switchable input attenuation allows input levels of up to +48 dBu, includes a ground lift switch, and is powered by 9V battery or 48V phantom power. DI20 LIST 29.99



FULL DISCOUNT WHOLESALE



The DI100 features input buffering, & the renowned OT-1 output transformer.

Direct connection of amplifier outputs with ratings of up to 3,000 Watts. Internal battery automatically shut off when phantom power is connected. Świtchable input attenuation allows input levels of up to +50 dB w/ ground lift. LIST DI100-ULTRA-DI .39.99

#### **CALL FOR PRICE**



Your choice of either four or eight professional DI channels in one rack space. An XLR and a 1/4" TRS input, and a balanced output XLR and 1/4" TRS output per channel. Up to 40 dB of switch-able attenuation and up to 20 dB of gain. Allows direct connection to speaker outputs at up to 3000 Watts. Includes phase reverse and ground lift switches. LIST

#### DI4000-ULTRA-DI-PRO

Four DI channels in a single RU ......99.99 DI800-ULTRA-DI

Eight DI channels in a single RU ......99.99 CALL FOR PRICE



### Countryman

Provides the ultimate way to connect guitar pickups, contact mics or electric instruments to a recording

or PA console without loss of audio quality. Does not load the signal from your pickup, no loss of level or increased distortion. The case is made of indestructible extruded aluminum, recessed connectors and switches, battery or phantom power, internal pad for speaker bridging, true ground isolation, RF filtered. .231.70 DT85

#### **CALL FOR PRICE**



3.5mm mini-jack inputs (all parallel). HIGH/ LOW switch (-20dB pad). 1/4" phone jack line output. XLR male isolated miclevel output with GND/LIFT switch.

LIST .....Mobile interface box.....130.49 AV1A AVP-1STS .... A/V interface w/ steel wallplate/mountable .....114.99 AVP-1VSTS ... A/V interface w/ volume control......161.99



# 

Affordable and versatile. Features 1/4" HI-Z input\_and loop-through output, a LO-Z output and a ground-lift switch. Packaged in a durable 16 gauge steel box. LIST 62.49



### 🕼 PRO CO **Interface Boxes DB-1 Direct Box**

1/4" phone jack input, 1/4" phone jack parallel output. SPKR/INST switch (-20dB pad). FILTER/FLAT switch (six dB/octave low pass), XLR male isolated output with GND/LIFT switch. LIST 106.99.....

#### 🕼 PRO CO MC-2 Mic Combiner



Two XLR female inputs, input #two POL/REV switch, XLR male isolated outputs with GND/LIFT switches. Pro-Co MBT-1. LIST 131.99 .....

### 🕼 PRO CO **MS-2/MS-3** Mic



### **Splitters**

Female XLR input, XLR male 1-direct & 1-isolated (w/groundlift) output (MS-2), or 1-direct & 2isolated (w/groundlift) outputs (MS-3), both use the Pro Co MBT-1 transformer.

	LIST
MS2-PROCO1x2 mic splitter	100.49
MS3-PROC01x3 mic splitter	123.29

### 🕼 PRO CO **MS42A/MS43A**

### **Rackmount Mic Splitters**

These split mic signals for 2 or 3 mixers. 4female XLR mic inputs, 2 outputs (MS42A) or 3 outputs (MS43A), 1-direct & 1 or 2 isolated (w/groundlift) XLR outputs. LIST MS43A .......4x3 rackmount splitter ......417.49

**CALL FOR PRICE** 

# CONFIDENTIAL

The prices in this catalog are only for:

- CONTRACTORS
- AV DEALERS
- RETAILERS
- SYSTEM INTEGRATORS
- SECURITY INSTALLERS

FULL DISCOUNT WHOLESALE 800-828-0509 LOCAL: 608-831-1946 8AM-8PM M-F CST | 10AM-4PM SAT CST



CONNECTORS



# SPLITTERS/COMBINERS/DIRECT BOXES/ACCESSORIES





### ROLLS DB14/DB25 Direct Boxes

The DB14 is a special purpose direct box for applications where a stereo signal can be separated, and individual volume controls used for each track such as rehearsing a choir to a music track. It has stereo RCA inputs, 2 volume controls, RCA and XLR outputs, and uses no power. The DB25 is a transformer-balanced, passive direct box featuring an attenuator, paralleled 1/4" Input jacks and a ground lift. LIST

DB14.....Director.... **CALL FOR PRICE** 

### ROLLS] PB224 Phantom Power Supply



. 70.00

Perfect for any condenser microphone, the PB224 powers even the high-current draw microphones. The unit features a rock solid 48 volts of clean phantom power. It can operate from two internal 9V batteries or from the Rolls PS27 AC adapter. LIST PB224 .....2-channel phantom power supply ....120.00

**PS27** ......AC adapter .....10.00 **CALL FOR PRICE** 



The SE162 Red Square is an instrument direct box/impedance matching device with a sonic exciter built in. The unit works as any direct box with a 1/4" input and XLR and 1/4" output, but the SE162 features a bypassable sonic exciter with a Bottom control for adjusting the "punch" and Definition control which adjusts the clarity and presence of the signal. LIST 110.00

### t YOUR OFFSITE SERVICE DEPARTMENT

.....

We can get your clients back up and running. Full Discount is your factory-authorized service center for Akai, Allen & Heath, Community, Crown, EV, JVC, Mackie, Marantz, Panasonic, QSC, Roland, Samson, Sony, Spirit by Soundcraft, Soundcraft, Tascam, and Teac. Call and ask for SERVICE today.

#### Shure **Problem Solvers** Switchable microphone attenuator prevents pream plifier overload when strong signals are applied. Provides 15, 20, 0r 25 dB of microphone attenuation, passes phantom power and requires use of balanced signals; XLR female in and XLR male out. LIST A15AS... 45 62 Bridging transformer matches balanced or unbal-anced devices of different impedances. 33 kilohm primary: 600 or 7500 ohm secondary; may be used in reverse. Slender in-line XLR (F) to XLR (M) configuration. A15BT LIST 55.95 High-pass filter reduces unwanted noise in micro phone signals. Provides low-end roll-off of 12 dB per octave below 100 Hz. Slender, in-line XLR (F) to XLR (M) configuration. Requires use of balanced signals. A15HP LIST 52.50 Line adapter provides 50 dB attenuation, allowing a balanced line-level source to be connected to a balanced microphone input. Slender, in-line XLR (F) to XLR (M) configuration. Requires use of balanced signals. LIST A15LA......41.37 Switchable phase reverser provides instant switch selection of normal or reversed phase of a balanced line without modification of equipment. Reverses polarity of pins 2 and 3 of a balanced line. Slender, in-line XLR (F) to XLR (M) configuration; may be used in reverse. Requires use of balanced signals. LIST A15PRS.. 52 50 Tone generator produces a continuous 700 Hz miclevel signal capable of driving low-impedance, bal-anced lines. 1,000 hours of battery life under continuous use. On/Off switch, XLR male output. LIST Economy low- to high-impedance microphone matching transformer provides 24 dB of voltage gain and may be used in reverse. Balanced 3-pin XLR female input, built-in 1/4" male phone plug LIST output. A85F... 19.62 Low- to high-impedance microphone transformer provides 24 dB of voltage gain and may be used in reverse. Balanced 3-pin XLR female input, Am-phenol MC1M-type output connector with mating 1/4 jack and phone plug adapters. LIST A95UF..... 42.17 Same as A95UF, but with 3-pin XLR male low-impedance connector. A95U .38 47 Ager Low- to medium-impedance microphone trans-former with mini-plug output connector. Adapts a balanced, low-impedance microphone to cam-corder/recorder input. 3-pin XLR female input con-nector; 2-circuit, 3.5mm mini-plug output connec-tor with 18-inch (45 cm) cable. LIST Ager 53.58 A96F ..... 53 58 A120S Accessory in-line switch provides on/off, push-totalk, cough button, and transmitter relay keying functions for wired microphones. Convenient handheld size with belt clip. For hardwired, in-line use with various cable diameters. LIST A120S..... 28 11

CALL FOR PRICES ON ALL SHURE PROBLEM SOLVERS



FULL DISCOUNT WHOLESALE

CONNECTORS

HEADPHONES

MIXERS

CD PLAYERS

RECORDERS

SIGNAL PROCESSING

AMPLIFIERS

SPEAKERS

VIDEO

LIGHTING

STANDS

FURNITURE

CASES/BAGS

POWER

TEST EQUIPMEN

TOOLS

15

Radial make no-compromise DI's used by professionals for both studio and live applications. Transparency and clarity of signal is what they strive for using ultra-high quality/low distortion components and have amazing frequency response from 10Hz to up to 80kHz! Available in several configurations to meet your specific requirements. All boxes feature heavy duty 14 gauge steel boxes, XLR/1/4" TRS & unbalanced connectors, and a 3-year warranty.

Boxes

		LIJI
	Combo phono preamp & direct box	200.00
100 MV2	Transformerless DI, 15dB pad, 48V phani	200.00 tom
J40-IVINZ	Italisionneness Di, 1500 pau, 407 pilani nowar ground lift mix marga, 10 40kHz	200.00
	power, ground lift, mix-merge, 10-40kHz Passive DI, polarity reverse, ground lift, pa	200.00
JUV-IVIK3	Passive DI, polarity reverse, ground lift, pa	10,
	passive mix/merge, Jensen JT-DB-EPC	150.00
	xformer, 10-80kHz Passive DI, ground lift, Jensen xformer,	450.00
JDI-MK3	Passive DI, ground lift, Jensen xformer,	
	10-80kHz Stereo version of the JDI	200.00
JDI-DUPLEX	Stereo version of the JDI	350.00
JD6	Six channel rack mounted version	
	of the JDI	900.00
JD7	Jensen transformer guitar level distributio	n
	to feed up to seven amps simultaneously,	with
	push button selection, and balanced I/O	
	for record and playback of existing tracks	1000.00
JPC	Two channel active/transformer DI with 1/	8".
	1/4" and RCA inputs for interfacing comp	
	and consumer audio gear	
PRODI	Transformer-coupled passive direct box	
	Active Class-A re-amplifying device, with J	
A AM	in/1/4" out to feed guitar amps from balar	nced
	line sources. Line level control, overload	1000
	LED and ground lift options	
D2I-NIWT	Two channel line-level isolation box with	200.00
14111-150	Jensen transformers, 15 dB pad and	
	separate ground lifts	250.00
16.5	High quality Jensen transformer equipped	230.00 1 mic
JJZ	splitter, withXLR input, thru, and an isolat	od .
	monitor output. A fourth output is a thru	eu
	with ground lift switching	225 00
16.2	with ground lift switching Like JS-2 but with input, thru and two	229.00
199	LIKE JS-2 DUL WILLI INPUL, LITU AND LWO	250.00
	transformer isolated outputs	250.00
J-KAK	A 2 RU rack chassis that mounts up to ei	gnt
	Radial DIs, drivers, or splitters side by sid	
	Units may be mounted with either the inp	
	or output side facing front as desired	125.00
	CALL FOR PRICE	



We have parts for every manufacturer's product that we sell. Give us a call & let us know what you are looking for. 1-800-828-0509 extension 1358

# SPLITTERS/COMBINERS/DIRECT BOXES/ACCESSORIES



# RECORDERS

SIGNAL PROCESSING

























TOOLS



CONNECTORS

16



Get rid of your microphones! The ADB-1 allows a Hi-Z unbalanced source to directly feed to Lo-Z balanced input. The ADB-1 operates on either phantom power or a 9-volt battery. Features: flat response, low distortion, low noise, wide dynamic range (input will handle up to 6v P-P in instrument position), no transformer, RF protection on input and output, switchable ground isolation, flush mounted slide switches, full two-year warranty, designed and manufactured in the USA. LIST 109.00 .....

Use the Tapco DB series to connect your guitar or

bass direct to your mixer - without losing tone due

to impedance mismatches, low levels, and 60-

cycle hum. Thru/Out jack lets you send a clean signal to a mixer, plus an onstage amplifier, for greater control during live performance. The DB-1A can be

powered via 48V phantom power from a mixer or

internally via two 9-volt batteries (not included).

The DB-1P features a filter for enhancing bass and

DB1A ......Active .....CALL

**CALL FOR PRICE** 

.....Passive .....CALL

LIST

**DB1A and DB1P** 

**Direct Boxes** 

guitar sounds.

DB1P



**DIRECT-JT** A top-of-the-line passive DI featuring, the Jensen JT-DB-EPC:200k:1.5k



transformer-world renown for wide frequency response and superior noise rejection characteristics. Extruded aluminum ed Whirlwind durability. The 1/4<sup>+</sup> input jacks can be used as "INPUT / THRU" or they may be com-bined with the "COMBINE" pushbutton to safely sum stereo feeds to a single channel. The "FIL-TER / OFF" button engages a filter that emulates the frequency response of a microphone placed in front of a 12" speaker. The "PAD" button engages 15dB pad for reducing hot input levels. Also includes reverse phase and ground lift but-tons. THD @ 1kHz: less than 0.001%. LIST DIRECT-JT ..... .219.90

**CALL FOR PRICE** 

### whirlwind EDB1

An economy direct box offering rugged construction while maintaining exceptional sound quality. 1/4" in and through jacks, pad switch, and ground lift. Input impedance: 20k Öhms output impedance: 150 Ohms. EDB1 ....

CALL FOR PRICE



Hot Box This top-of-the-line DI is an

active direct box that operates from battery or phantom power. The Hot Box provides super-clean

front-end circuitry that delivers the the widest frequency response that you'll find in any direct box. Provided are a ground-lift switch, useful for eliminating ground-loop hum problems even with Phantom Power, and a switch that allows you to switch between instrument, line, or amplifier inputs

(passive) and 4 active destinations. A pair of

LIST 169.90 .....



### whirlwind AS8X4 Active Splitter

The Whirlwind AS8X4 microphone splitting system provides a new level of versatility for sys-tems requiring 5-way mic splitting for as few as 8 or as many as 80 channels. This system is based on rack mount modules, each having the capability of splitting 8 mic channels to 1 direct



high quality Lundahl transformers (Swedish) on each channel provides superior noise rejection and balancing, making this unit the ideal choice in applications where extremely long cable runs are required. Each channel features push-buttons for engaging a 20dB input pad, 48V phantom power and a button for placing the channel into "listen" mode which adds it to a headphone monitoring buss. A three step LED monitors available headroom. All connections are made via Phoenix terminal strips for easy, solderless, on site termination. Internal dip switches are provided for each channel which set ground lift status and provide 20dB, 30dB or 40dB of gain LIŠT boost. .2599.90 .....Rack mount 8 X 5 mic splitter...... AS8X4 ....Powers up to 4 AS8X4 units ..........2362.08 AS8PS4 AS8PS6 .....Powers up to 6 AS8X4 units ...... .2441.76 AS8PS10 ...Powers up to 10 AS8X4 units .......3004.68

**CALL FOR PRICE** 

### whirlwind PCDI

The PCDI is designed to interface your unbalanced stereo line sources with professional balanced low inpedance equipment.



Features 2 separate DI's, Inputs; 1-3.5mm (1/8") mini TRS stereo jack or 2 sets of color coded RCA in/thru. Output; color coded XLRs. Also features a ground lift and a 20dB pad. Perfect for interfacing with the outputs of CD players, computer sound cards, tape decks, etc. LIST PCDI ... 179.90

**CALL FOR PRICE** 

### whirlwind SPLIT 6

Use this handy box when you need to split a line level signal up to 6 times. Features 1 female XLR input wired to 6 male XLR outputs. Note: It is not recommended that the SPLIT 6 be used to split a microphone level signal to more than two outputs. LIST SPLIT6 .99.90

**CALL FOR PRICE** 

### whirlwind

LIST

27 90

SPLITTER-L The SPLITTER-L utilizes the Lundahl LL1581XL mic transformer for widest



frequency response and lowest noise. This is the same transformer used in the very best Custom Shop Super Concert splitters. It provides one direct and two transformer isolated outputs from one mic level input. The isolated outputs feature a ground lift button and a 20dB input pad button is provided to reduce hot signals. CMRR @ 20kHz: greater than 60dB. Frequency response is 10Hz-100kHz ±.5dB. LIST SPLITTER-L CALL

**CALL FOR PRICE** 

## t. YOUR OFFSITE SERVICE DEPARTMENT

We can get your clients back up and running. Full Discount is your factory-authorized service center for Akai, Allen & Heath, Community, Crown, EV, JVC, Mackie, Marantz, Panasonic, QSC, Roland, Samson, Sony, Spirit by Soundcraft, Soundcraft, Tascam, and Teac. Call and ask for SERVICE today.

FULL DISCOUNT WHOLESALE 800-828-0509 LOCAL: 608-831-1946 8AM-8PM M-F CST | 10AM-4PM SAT CST