



## BULK WIRE

## AUDIO – MICROPHONE CABLE, 2-CONDUCTOR SHIELDED

ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Belden	8412		20	26 x 34	.262"	30	85% Braid	EDPM Rubber
Gepco	MP1022		24	41 x 40	.195"		95% Braid Synth	Rubber
Mogami	W2549		22	30 x 37	.236"	23		Super Flexible PVC
Whirlwind	WMKPVC		22	26 x 36		35	78% BC Braid	Flexible PVC, black

## AUDIO – ANALOG MIC CABLE: 4-CONDUCTOR STAR-QUAD, LOW NOISE, FOR PORTABLE USE

ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Canare	L4E6S		24	40	.237"	46	95% Braid	PVC
Mogami	W2534		24	20 x 37		20	Spiral	Super Flexible PVC

## AUDIO – ANALOG MIC/LINE PERMANENT INSTALL, 2-CONDUCTOR, FOIL SHIELD WITH DRAIN WIRE

ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET	NEC
Belden	1503A		22	7 x 30	.142"	53	100% Foil	PVC	CM
Belden	8450		22	Solid	.118"	40	100% Foil	PVC	CM
Belden	9451		22	7 x 30	.135"	34	100% Foil	PVC *	CMR
Canare	L4E5AT		22		.197"	50	100% Alum. Tape	PVC	
Canare	L4E6AT		20		.244"	46	100% Alum. Tape	PVC	
Gepco	61801EZ		22	7 x 30	.140"	34	100% Foil	PVC	CMR
Mogami	W28062C		22	30 x 37	.205"	27	Self Stripping Foil	PVC, gray	
West Penn	291		22	7 x 30	.165"		100% Foil	PVC	CL2
West Penn	292		20	7 x 28	.184"		100% Foil	PVC	CL2
West Penn	293		18	7 x 26	.208"		100% Foil	PVC	CL2
West Penn	25291B		22	7 x 30	.165"		100% Foil	PVC	CMP
West Penn	25292B		20	7 x 28	.143"		100% Foil	PVC	CMP

\* Features self-stripping foil and BananaPeel- no jacket, just pull and peel.

## AUDIO – DIGITAL MIC CABLE: AES/EBU 2-CONDUCTOR SHIELDED, 110 OHMS, LOW CAPACITANCE

ITEM			GAUGE	STRANDING	O.D.	PF/FT	SHIELD	JACKET
Cable Up	AES7-500		24	7 x 30	.198"	14.5	95% Braid	Non-plen PVC
Canare	DA206		20		.287"	14.6	95% Braid	Non-plen PVC, blue

## AUDIO – ANALOG MIC/LINE MULTIPAIR (SNAKE), FOIL SHIELD, COMMON JACKET

ITEM			GAUGE	PAIRS	O.D.	PF/FT	SHIELD	JACKET	NEC
Gepco	6604HS		22	4	.285"	52	100% Foil/mylar side out	Plenum PVC	CMP
Gepco	6608HS		22	8	.385"	52	100% Foil/mylar side out	Plenum PVC	CMP









*Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.*

## BULK WIRE NEC RATINGS











CMP – Rated for all in-wall, plenum and riser applications. • CMR, CL3R, CL2R – Rated for all in-wall and riser applications, not permitted in plenums.  
 CM, CMG, CL2 – In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums.



**AUDIO – ANALOG MIC/LINE MULTIPAIR (SNAKE) WITH INDIVIDUAL JACKETS PER PAIR**

ITEM	GAUGE	PAIRS	O.D.	PF/FT	SHIELD	JACKET	NEC
<b>Gepco</b> - Call for Length information, some available by the foot (varies).							
Gepco	<b>GA61804GFC</b> 	22	4	.410"	60	PVC	CMR
Gepco	<b>GA61806GFC</b>	22	6	.480"	60	PVC	CMR
Gepco	<b>GA61812GFC</b> 	22	12	.960"	60	PVC	CMR
Gepco	<b>GA61820GFC</b>	22	20	.880"	60	PVC	CMR
Gepco	<b>GA61826GFC</b>	22	26	.950"	60	PVC	CMR
Gepco	<b>GA61832GFC</b>	22	32	1.115"	60	PVC	CMR
<b>Gepco</b> - Direct Burial series - for permanent underground installs, incl. water blocking tape that is wrapped around cable core, difficult to puncture.							
Gepco	<b>GA61806PEF</b> 	22	6	.475"	48	100% Foil	PVC/Base10
Gepco	<b>GA61812PEF</b> 	22	12	.635"	48	100% Foil	PVC/Base10
<b>Mogami</b> - Super flexible down to -2° C, channel #s printed & underlined on jacket to ensure correct ID. Ideal for soldering or crimping to connectors.							
Mogami	<b>W2932</b> 	25	8	.453"	40		PVC
Mogami	<b>W2934</b> 	25	16	.622"	40		PVC
Mogami	<b>W2936</b> 	25	24	.787"	40		PVC
Mogami	<b>W2938</b> 	25	32	.854"	40		PVC
Pro Co	<b>AC4</b>	24	4	.425"	21		PVC
Pro Co	<b>AC8</b>	24	8	.550"	21		PVC

**AUDIO – SPEAKER CABLE, PORTABLE HIGH FLEXIBILITY, HEAVY DUTY JACKET**

ITEM	GAUGE	COND.	O.D.	JACKET	NEC	DESCRIPTION
<b>Belden</b> - 2 Conductor, ultra flexible, ideal for home theater installs, jackets marked at 2' intervals. Black, white, gray blue or green jackets.						
Belden	<b>5000UP</b> 	12	2	.302"	PVC	CL3
Belden	<b>5200UP</b> 	16	2	.208"	PVC	CM
Canare	<b>4S8</b> 	16	4	.327"	PVC	General purpose, bi-amp rigs
Canare	<b>4S11</b> 	11	4	.421"	PVC	Long runs, subwoofers, gray only
<b>Gepco</b> - All-weather TPE outer jacket, round construction, ideal for Speakon.						
Gepco	<b>GSC132</b> 	13	2	.350"	TPE, black	
Gepco	<b>GSC134</b> 	13	4	.420"	TPE, black	
Gepco	<b>GSC138</b> 	13	8	.580"	TPE, black	
Pro Co	<b>11-4</b> 	11	4		PVC	
Pro Co	<b>14-4</b> 	14	4		PVC	
Pro Co	<b>13-8</b> 	13	8		PVC	
Pro Co	<b>14-2</b>	14	2		PVC	

*Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.*

AUDIO






COMPUTER AV













ACCESSORIES









## AUDIO – GUITAR / KEYBOARD / INSTRUMENT CABLE

ITEM	GAUGE	COND.	O.D.	PF/FT	SHIELD	JACKET
<b>Cable Up</b> - Guitar cable, low noise, low capacitance.						
Cable Up <b>M54C-500</b> 	20	1	.236"	37.2	PVC	Conductive PVC Layer
<b>Canare</b> - For electronic instruments, test probes, audio patch, and amp to cabinet leads.						
Canare <b>GS6</b> 	18	1	.228"	49	OFC >92% Braid	Carbon Sleeve
<b>Gepco</b> - Data-grade, foam dielectric (drastically reduces capacitance), abrasion resistant PVC.						
Gepco <b>XB20UB</b> 	20	1	.228"	22.3	Double 95% TC Braid	PVC



## AUDIO – UNSHIELDED CABLE: FOR SPEAKER AND CONTROL APPLICATIONS

ITEM	GAUGE	COND.	O.D.	STRANDING	JACKET	NEC
Belden <b>8471</b> 	16	2	.274"	19 x 29	PVC	CMG
Belden <b>8477</b> 	22	2	.386"	65 x 30	PVC	CL3R
Coleman <b>23288</b> 	12	2	.410"	65 x 30	T*Prene	
<b>Gepco</b> - Permanent Install – BC, PVC insulation, plenum only shown (call for others).						
Gepco <b>IP122BA19</b> 	12	2	.258"	19 x 25	Plenum PVC, white	CL3P
Gepco <b>IP162BA19</b> 	16	2	.170"	19 x 29	Plenum PVC, white	CMR
West Penn <b>224</b> 	18	2	.186"	7 x 26	PVC	CL2, CMR
West Penn <b>225</b> 	16	2	.204"	19 x 29	PVC	CL2, CMR
West Penn <b>226</b> 	14	2	.240"	19 x 27	PVC	CL2, CMR
West Penn <b>227</b> 	12	2	.278"	19 x 25	PVC	CL2, CMR
West Penn <b>25224B</b> 	18	2	.138"	7 x 26	Plenum	CMP

## AUDIO – S/PDIF DIGITAL AUDIO CABLE – 75 OHM

ITEM	GAUGE	STRANDING	O.D.	PF/FT	JACKET	NEC
Belden <b>1505F</b> 	22	7 x 29	.242"	17	PVC Black	CM
Gepco <b>VDM230</b> 	Mini23	Solid	.164"	16.5	PVC, Multiple Colors	CMR
Gepco <b>VHD1100</b> 	RG11/14	Solid	.405"	16.2	PVC, Multiple Colors	CMR
Gepco <b>VHD2000M</b> 	21	19 x 34	.242"	17	Flexible PVC	
Gepco <b>VSD2001</b> 	RG6/18	Solid	.272"	16.3	PVC, Multiple Colors	CMR
Gepco <b>VPM2000</b> 	RG59/20	Solid	.272"	16.3	PVC, Multiple Colors	CMR

## AC – POWER CABLE FOR PORTABLE USE

ITEM	GAUGE	COND.	JACKET
Coleman <b>23387</b> 	14	3	T*Prene SJEW
Coleman <b>23388</b> 	12	3	T*Prene SJEW




*Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.*

## BULK WIRE NEC RATINGS









**CMP** – Rated for all in-wall, plenum and riser applications. • **CMR, CL3R, CL2R** – Rated for all in-wall and riser applications, not permitted in plenums.  
**CM, CMG, CL2** – In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums.







LIGHTING – DMX CABLE – BULK

ITEM			GAUGE	COND.	STRANDING	O.D.	SHIELD	JACKET	NEC
Belden	<b>9841</b>		24	4	7 x 32	.232"	100% Foil + 90% TC Braid	PVC	CM
Belden	<b>9842</b>		24	4	7 x 32	.340"	100% Foil + 90% TC Braid	PVC	CM
Gepco	<b>DLC224</b>		24	4	7 x 32	.270"	100% Foil + 90% TC Braid	PVC	






DATA – CAT5E AND CAT6 BULK CABLE

ITEM			TYPE	GAUGE	COND.	PAIRS	O.D.	PF/FT	STRANDING	JACKET	NEC
Belden	<b>1583A-1000</b>		Cat5e	24	8	4	.214"	15	Solid	PVC	CMR
Belden	<b>1585A-1000</b>		Cat5e	24	8	4	.200"	15	Solid	Plenum	CMP
Belden	<b>1872A-1000</b>		Cat6	23	8	4	.365"	15	Solid	PVC	CMR
Belden	<b>1874A-1000</b>		Cat6	23	8	4	.365"	15	Solid	Plenum	CMP
Gepco	<b>CT504/360</b>		Cat5e	24		4	.200"		Solid	PVC	CMR
Gepco	<b>CT504/360P</b>		Cat5e	24		4	.180"		Solid	Plen PVC	CMP
Gepco	<b>CT504HD</b>		Cat5e	24		4	.260"	17	41 x 40	TPE, black	
Gepco	<b>CT504HDX</b>		Cat5e	24		4	.245"	17	Solid	TPE, black	



DIGITAL/ANALOG VIDEO – 75 OHM SDI/HDSOI COAXIAL CABLE – RG6

ITEM			GAUGE	STRAND	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC
Belden	<b>WV-1694D</b>		2 x 18	Solid	.334" x .618"	16.2	82%	100%Duofoil+95%TCBraid	Non-plenum	CMR
Belden	<b>1694A</b>		RG6/18	Solid	.275"	16.2	82%	100%DuoFoil+95%TCBraid	Non-plen PVC	CMR
Belden	<b>1695A</b>		RG6/18	Solid	.234"	16.2	82%	100%DuoFoil+95%TCBraid	Plenum	CMP
Canare	<b>L4CFB</b>		RG59/20	Solid	.240"	17	79%	100%Foil/93%Braid	PVC	

DIGITAL/ANALOG VIDEO – 75 OHM SDI/HDSOI COAXIAL CABLE – RG59

ITEM			GAUGE	STRAND	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC
Belden	<b>1505A</b>		RG59/20	Solid	.233"	16.3	83%	100%DuoFoil+95%TCBraid	Non-plen PVC	CMR
Cable Up	<b>RG59ST-500</b>		RG59/22	7 x 29	.242"	17.0	80%	Double TC Braid 95%	Non-plen PVC	CM
Gepco	<b>VPM2000</b>		RG59/20	Solid	.242"	16.3	83%	100%Foil/95%TCBraid	Non-plen PVC	CMR
Gepco	<b>VPM2000TS</b>		RG59/20	Solid	.200"	16.0	84%	100%Foil/95%TCBraid	Plen PVC	CMP
Gepco	<b>VHD2000M</b>		RG59/21	19 x 34	.242"	17	78%	95%TC Braid dbl-shield Flex.	Non-plen PVC	

VIDEO – RG-59/8281F TYPE (STANDARD & PLENUM) SINGLE CHANNEL

ITEM			GAUGE	STRANDING	O.D.	PF/FT	VEL-PROP	SHIELD	JACKET	NEC
Belden	<b>8241</b>		RG59/23	Solid	.242"	21	66%	95%Braid	PVC	CM
<b>Canare</b> - Highly flexible, cooper braid shield polyethylene dielectric										
Canare	<b>LV61S</b>		RG59/24	7/7.88	.240"	21	66%	95% Braid	Poly	

Bulk wire is available in standard spool lengths, and some can be cut to your requirements. Please call for specifics.

