

AUDIO



COMPUTER AV



VIDEO



Littlite


LITTLITE L-SERIES SETS L-Series lighting sets come complete and ready for surface mounting. Available in 6", 12", or 18" lengths with bulb, mounting base, dimmer, 6' cord, 2-piece snap mount, screws for permanent mounting and a wall plug-in transformer. "A" versions are available without the transformer and can be powered by any available 12V supply.

THE L-1 features detachable gooseneck swivel connector at the base and gooseneck storage clips. The lamp has a low intensity incandescent bulb in tubular hood.

THE L-2 features a permanently attached gooseneck with a low intensity incandescent bulb in an unobtrusive tubular hood.

THE L-3 features a permanently attached gooseneck with a high intensity tungsten-halogen bulb in a stylish finned hood.

THE L-4 features a detachable, gooseneck swivel connector at the base and gooseneck storage clips. Lamp has a high-intensity, tungsten-halogen bulb in a finned hood.



LITTLITE INDIVIDUAL GOOSENECK LAMPS

Littlite G, P and X Series gooseneck lamps can be built into any device that requires lighting. Available in 6", 12" and 18" lengths. Low low-intensity and high-intensity versions available.

G-SERIES Goosenecks have a swivel connector, and are useful in applications requiring removal for transit or storage. They mate with panel sockets supplied on or added to equipment.

P-SERIES Goosenecks have a 3/8" diameter (1/8" NPT) threaded end with ground lug and nut. Use where a permanently mounted gooseneck is desired. Mounts in a 3/8" hole in material up to 1/8" thick. Add an MP for mounting in thicker material.

X-SERIES Goosenecks have a 3-pin male XLR-type connector with isolated lamp circuit. Useful where a detachable, non-swiveling connection is desired. Ideal for sloped or vertical work surfaces. Wired as follows: Pin 1-case, pin 2-lamp, pin 3-lamp.




LITTLITE ACCESSORIES

ITEM	DESCRIPTION	PRICE
1815	Standard bulb 12V 230ma 2.4W	3.25
CF	Color filter set	3.99
CL	Adjustable clip for "L" models	14.81
DM	Dimmer, 3/8" mounting	12.02
GPK	Dimmer base for BNC lamps	39.90
HH	High hood replacement	8.24
HTC	High tension clamp	10.29
MB	Magnetic base	16.01
MP	Mounting plate with 3/8" hole	5.15
O-KIT	O-ring kit	3.15
PS	BNC panel socket	5.72
Q5	High-intensity bulb 12V 280ma 5W	9.00
SC	Storage clips, pair	3.73
SM	Snap mount for "L" models	3.99
CWB	Weighted base	26.00

LITTLITE L.E.D. GOOSENECK LIGHT Low power (<100 milliamps), high output, long life (>5000 hours), and wide area illumination are the key points to this new addition to the Littlite family. Lampsets are switchable to red only.

ITEM	DESCRIPTION	PRICE
L12-LED	12" lamp w/dimmer & mount	99.47
L18-LED	18" lamp w/dimmer & mount	99.47
L2G-LED	12" detachable lamp (BNC)	65.98
L2G-LED	12" detachable lamp (BNC)	65.98
L2X-LED	12" detachable lamp (3-pin XLR)	76.38
L2X-LED	12" detachable lamp (3-pin XLR)	76.38
L2X4-LED	12" detachable lamp (4-pin XLR)	78.16
L2X4-LED	12" detachable lamp (4-pin XLR)	78.16



Littlite

LITTLITE COMPLETE KITS

ITEM	DESCRIPTION	PRICE
L1/12	12" detachable, dimmer, transformer, base	66.05
L1/12A	Without transformer	54.81
L1/18	18" detachable, dimmer, transformer, base	66.05
L1/18A	Without transformer	54.81
L2/6	6" base mounted, dimmer, transformer	54.81
L2/12	12" base mounted, dimmer, transformer	54.81
L2/12A	Without transformer	43.68
L2/18	18" base mounted, dimmer, transformer	54.81
L2/18A	Without transformer	43.68
L3/6	6" high-intensity, base, dimmer, transformer	66.05
L3/12	12" high-intensity, base, dimmer, transformer	66.05
L3/12A	Without transformer	54.81
L3/18	18" high-intensity, base, dimmer, transformer	66.05
L3/18A	Without transformer	54.81
L4/12	12" high-intensity, detachable, dimmer, transformer	77.23
L4/18	18" high-intensity, detachable, dimmer, transformer	77.23

LITTLITE INDIVIDUAL LIGHTS

ITEM	DESCRIPTION	PRICE
6G	6" with BNC connector	32.29
6P	6" with 3/8" connector	26.88
6X	6" detachable w/ XLR connector	38.74
12G	12" with BNC connector	32.29
12G-HI	12" BNC high-intensity	43.58
12P	12" with 3/8" threaded end	26.88
12X	12" detachable w/XLR connector	38.74
12X-4	12" with 4-pin XLR	53.29
12X-HI	12" 3-pin XLR high-intensity	50.04
12X-HI-4	12" high intensity 4-pin angle lamp	64.05
12XR-HI	12" high intensity 3-pin angle lamp	63.21
18P	18" with 3/8" threaded end	26.88
18G	18" with BNC connector	32.29
18G-HI	18" BNC high intensity	43.58
18X	18" detachable w/XLR connector	38.74
18X-4	18" with 4-pin XLR	53.29
18X-HI	18" 3-pin XLR high intensity	50.04
18X-HI-4	18" 4-pin XLR high intensity	64.05
18XR	18" detachable angle lamp	52.03
18XR-HI-4	18" 4-pin XLR right angle	78.33

MIGHTY BRIGHT



MIGHTY BRIGHT MUSICIAN'S LIGHTS

XTRAFLEX DUET™ DUET2 LED MUSIC LIGHT These dual super LED lights with two adjustable goosenecks can light two pages at once. Clips easily to almost anything and offers 20 hrs of continuous use. The Duet2 offers 4 different light level options.

ITEM	DESCRIPTION	PRICE
50810	XtraFlex Duet dual LED gooseneck lights, black	28.00
51810	Duet2 dual LED gooseneck lights, black	46.00
80910	Light cradle/stand-alone base for XtraFlex lights, Duet lights, black	5.75

TRIPLE LED™ TELESCOPING 3 LED lenses focus light evenly. Fully extendable arm and maneuverable head allows you to position your music light over your score.

ITEM	DESCRIPTION	PRICE
50212	Silver w/ gig bag	28.00
50210	Black w/ gig bag	28.00
37372B	AC adaptor	11.50

CLASSIC SIGHT READER™ The original Mighty Bright. An economic solution for low-light situations. Features fully adjustable incandescent light beam.

ITEM	DESCRIPTION	PRICE
52212	Silver	13.44
52210	Black	13.44
36304	Replacement bulbs 2-pack	4.78
36332	AC adaptor	11.20

XTRAFLEX™ SUPER LED Super LED can be positioned in any direction. Special lens spreads light evenly with no hot spots.

ITEM	DESCRIPTION	PRICE
50412	Silver	16.80
50410	Black	16.80



Follow us!

Let us show you exactly what to expect with our lighting design computer modeling & pre-visualization.