



ROSCO DELTA 3000 FOG MACHINE

Capable of filling many stages in less than a minute, the Delta 3000 is made of a cast aluminum heat exchanger that houses a 1500W heater element. Rosco's Delta technology allows you to treat the fog machine's controls as you would a light fixture's controls by starting and ending it on cue. The Delta 3000 is controlled via digital DMX remote, analog DMX remote, or timed remote- any of which must be purchased in order to operate the machine.

ITEM	DESCRIPTION	PRICE
DELTA-3000	Fog machine	839.06
DELTA-3000-CASE	Case for Delta 3000	394.74
REMOTE-DELTA-DIGITAL	Digital DMX remote for Delta 3000	474.88
REMOTE-DELTA-ANALOG	Analog DMX remote for Delta 3000	303.95
REMOTE-TIMED	Timed remote for Delta 3000	303.95
08200-0034	Fog fluid, 1 liter	16.95



ROSCO DELTA HAZER The Delta Hazer uses a water-based fluid and can quickly fill venues of varying size thanks to its 1000W heat exchanger and its high quality blower. One knob regulates the fan and pump speed, varying the two for optimum output and allowing it to run continuously at high speeds. Also features continuous self-cleaning, onboard DMX, a low fluid sensor, and auto timers.

ITEM	DESCRIPTION	PRICE
DELTA-HAZER	Haze machine	1246.88
DELTA-HAZE-FLUID	Haze fluid, 4 liter bottle	58.45
REMOTE-DELTA-DIGITAL	Digital DMX remote	474.88
REMOTE-DELTA-ANALOG	Analog DMX remote	303.95
REMOTE-TIMED	Timed remote	303.95



ROSCO I-CUE INTELLIGENT MIRROR

The Rosco I-Cue is an intelligent mirror accessory designed to allow users of ellipsoidal spotlights to achieve many of the moving light effects traditionally available with automated fixtures. The unit is controlled via DMX 512 in 8-bit or 16-bit resolution. The moving mirror head offers smooth pan and tilt, as well as quick response re-positioning. The Rosco I-Cue ships ready to fit ETC Source Four, Altman Shakespeare, Strand SL, Selecon Pacific or any other light fixture with a 6.25" gel slot.

ITEM	DESCRIPTION	PRICE
I-CUE	Intelligent mirror	677.63
PSU-50	I-CUE power supply	132.97



ROSCO IPRO IMAGE PROJECTOR™


The iPro Image Projector™ projects images created from simple plastic slides. These iPro Slide cartridges are then attached to the back plate of the iPro and inserted it into the iris slot of any one of several common luminaires. Even at 100% intensity, the iPro Slide will last from 15-50 hrs with no fading or degradation. Choose any image from the Rosco iPro Slide Library (over 400 designs in 14 categories) or order a custom iPro Slide from your design. For last minute changes, an iPro Slide Kit is also available with easy instructions to design and print slides on-site.

ITEM	DESCRIPTION	PRICE
IMAGE-PRO-PROJECTOR	Image projector	287.63
HYBRID-TWO-FER	Power supply, allows you to connect the iPro and your light fixture into the same dimmer	53.57
IPRO-SLIDE-KIT	1-time slide kit which includes the slide mount and protective film to make an iPro slide with transparency film (not included) and your own printer	28.28
IPRO-SLIDE-LIBRARY	More than 400 images that can be made into an iPro slide, 24hr turnaround	38.03
IPRO-CUSTOM-SLIDE	Turns your own design into an iPro slide, 24hr turnaround	38.03



GLOBAL TRUSS SQUARE TRUSS

- 11-7/16" overall width
- 2" outer diameter of tubing
- 3/4" diagonal bracing
- 0.008" tubing wall thickness
- 1 set of connecting hardware included



ITEM	DESCRIPTION	PRICE
SQ4109	1.64' square truss	146.30
SQ4110	3.28' square truss	186.20
SQ4110-75	2.46' square truss	159.60
SQ4111	4.92' square truss	246.05
SQ4111-1250	4.10' square truss	206.15
SQ4112	6.56' square truss	285.95
SQ4112-2.15	7.05' square truss	292.60
SQ4112-BLK	6.56' square truss, black	345.80
SQ4113	8.2' square truss	332.50
SQ4114	9.84' square truss	365.75
SQ4115	11.48' square truss	418.95
SQ4116	13.12' square truss	465.50
SQ4117	14.76' square truss	505.40
SQ4118	16.4' square truss	551.95

GLOBAL TRUSS TRIANGULAR TRUSS

- 11-7/16" overall width
- 2" outer diameter tubing
- 3/4" diagonal bracing
- 0.008" wall thickness
- 1 set of connecting hardware included



ITEM	DESCRIPTION	PRICE
TR4076	1.64' triangular truss	126.35
TR4077	3.28' triangular truss	166.25
TR4078	4.92' triangular truss	199.50
TR4079	6.56' triangular truss	226.10
TR4080	8.2' triangular truss	252.70
TR4081	9.84' triangular truss	279.30
TR4083	13.12' triangular truss	352.45
TR4084	14.76' triangular truss	385.70
TR4085	16.4' triangular truss	425.60



SQ4133



COUPLER-CLAMP



PRO-CLAMP



TRIGGER-CLAMP



TR4108

GLOBAL TRUSS CLAMPS AND ACCESSORIES

ITEM	DESCRIPTION	PRICE
PRO-SWIVEL-CLAMP	2" diameter swivel clamp	28.00
TRIGGER-CLAMP	Heavy-duty hook style clamp	21.00
PRO-CLAMP	2" diameter aluminum fixture clamp	18.20
JR-CLAMP	1-1/3" diameter aluminum clamp	7.00
JR-SWIVEL-CLAMP	Light-duty swivel clamp	14.00
EYE-CLAMP	2" diameter aluminum clamp w/ eyebolt	21.00
COUPLER-CLAMP	2" diameter aluminum clamp w/ half coupler	19.60
COUPLER	Double ended coupler for connection of truss sections	11.20
SQ4137	Base plate for square truss	53.20
TR4108	Base plate for triangular truss	39.90
SQ4121	2-way 90° corner block for square truss	231.00
SQ4123	2-way 135° corner block for square truss	259.35
SQ4126	3-way 90° corner block for square truss	305.90
SQ4129	3-way T-junction for square truss	305.90
SQ4133	4-way cross-junction for square truss	332.50
TR4086-U/D	2-way 45° corner for triangular truss, apex up or down	259.35
TR4088-U/D	2-way 90° corner for triangular truss, apex up or down	206.15
TR4088-I	2-way 90° corner for triangular truss, apex in	206.15
TR4089-U/D	2-way 120° corner for triangular truss, apex up or down	203.00
TR4090-U/D	2-way 135° corner for triangular truss, apex up or down	192.85
TR4093-U/L	3-way 90° corner for triangular truss, apex up	266.00
TR4093-U/R	3-way 90° corner for triangular truss, apex up	266.00
TR4096H-U/D	3-way horizontal T-junction for triangular truss, apex up or down	272.65
TR4100-U/D	4-way cross-junction for triangular truss, apex down	272.65





JAMES THOMAS ENGINEERING FOLDING SUPERTRUSS

Supertruss has been developed for those applications requiring good load bearing capability in a compact size. The truss ladders are separated at the bottom by folding locking elbows and are hinged at the top with a custom made extrusion. All sections fold flat to a width of 5.25" to take up the smallest amount of space possible.

ITEM	DESCRIPTION	PRICE
B3660	12 foot 20.5" folding Supertruss	1603.41
B3661	10 foot 20.5" folding Supertruss	1423.15
B3662	8 foot 20.5" folding Supertruss	1320.49
B3663	6 foot 20.5" folding Supertruss	1306.31
B3664	4 foot 20.5" folding Supertruss	1227.74

JAMES THOMAS ENGINEERING PRE-RIG TRUSS

Pre-Rig truss is 30" x 26" in size. Each truss piece has 4 castor wheels for easy maneuverability and bolts for the connection of segments. Pre-Rig truss is designed to carry 2 lighting bars complete with fixtures. The lighting bars are stored internally in the truss and are lowered to the working position when in use. This design reduces the amount of space required for lighting and rigging in the truck. Each truss is also designed to carry a varying amount of fixtures: the 10' section carries 2 bars of 8, 7" 7" section carries 2 bars of 6, 5' section carries 2 bars of 4, and the 3' 9-1/2" section carries 2 bars of 3, enabling great flexibility in the truss design. Pre-Rig truss accepts modified lighting bars with 2 sleeved holes in them. The lighting bars are located inside the truss by guide rods. In the storage position the bars are securely held in the truss by shank hooks. Fixtures are not included.

ITEM	DESCRIPTION	PRICE
B0300	10' section	1433.33
B0301	7' 7" section	1283.16
B0302	5' section	1143.18
B0303	3' 9 1/2" section	1056.62
B4300	2-way corner block	925.68
B4301	4-way corner block	820.93

JAMES THOMAS ENGINEERING GENERAL PURPOSE TRUSS

12" x 12" general purpose truss manufactured from 2" diameter x 0.125" wall aluminum tubing. Bolts are supplied for assembly of truss elements. This truss is ideal for conference, exhibition, and small venue work. By incorporating suitable sleeve blocks and towers, this truss can be used with JTE's Ground Support System.

ITEM	DESCRIPTION	PRICE
B0700	10' section	801.71
B0701	8' section	698.09
B0702	5' section	559.06
B0703	2'6" section	426.21
B4700	3 meter section	801.71
B4701	2.5 meter section	698.09
B4702	2 meter section	628.58
B4703	1.5 meter section	559.06
B4704	1 meter section	479.46
B4705	2-way corner block	318.33
B4705A	3-way corner block	386.80
B4706	4-way corner block	449.27
B4707	6-way corner block	650.76



STAGEMAKER

STAGEMAKER CONCERT HOISTS

The Stagemaker concert hoists are designed for handling stage and theatrical equipment, enabling safe and accurate positioning of speakers, lighting systems, stage sets and sceneries. The hoists are CSA approved (configurations B and S only) and CE marked. The Stagemaker's light weight makes it ideal for touring events and the compact size permits it to fit inside truss structures. It's even quiet enough to operate during an actual theater performance. Various configurations are available to meet your specific application.

CALL YOUR SALES PRO TO TALK ABOUT AVAILABLE CONFIGURATIONS, OPTIONS, PRICING AND LEAD TIME.



PLEASE CALL FOR YOUR **FREE APOLLO**
SWATCHBOOK AND GOBO CATALOG

800-356-5844



ALTMAN LIGHTING, INC.

ALTMAN FIXTURE ACCESSORIES

ITEM	DESCRIPTION	PRICE
510	C-clamp for 3/4" to 1-1/2" pipe	CALL
510HD	Heavy-duty C-clamp for 1/2" to 2" pipe	CALL
SC-36-BK	Black safety cable with spring clip	CALL
6-CFB	Gel frame for 650/1KAF/360Q Series, S6-1535Z, S6-3055Z, PAR38, PAR56	CALL
8-CFB	Gel frame for 750 Series, PAR64	CALL
360-PH	Gobo holder for 360Q, S6, S6C & 4.5 Series (Channel Style)	CALL
6-BD-4	4-door, 8-leaf: 65Q Series, 1KAF Series, PAR38, PAR56, UV250	CALL
8-BD-4	4-door, 8-l eaf: 75Q, PAR64, PAR64-AL, PAR56/64-EA, UV-705, & SP Series	CALL
6-DN	Donut for 360Q Series	CALL



APOLLO EZ IRIS DMX Allows designers to conveniently adjust the beam of light from many conventional ellipsoids. Designed for use in lighting fixtures up to 750W; including ETC S4, Altman Shakespeare, and Strand SL.

- Smooth actuation provides seamless aperture changes
- Gear-driven for positive operation
- Black, powder-coat 22-gauge steel for rigidity and durability
- Addressable from DMX 1-512

ITEM	DESCRIPTION	PRICE
AC-EZ-IRIS	EZ Iris DMX	381.29
AC-SP-75W	Single power supply for EZ Iris	124.83

APOLLO 4-PIN CABLES High quality, durable cable with 4-pin XLR connectors for effective transfer of data and power from various lighting related accessory products such as rotators and scrollers.

ITEM	DESCRIPTION	PRICE
AC-4CABLE-3	4-pin accessory cable, 3 ft.	24.97
AC-4CABLE-10	4-pin accessory cable, 10 ft.	32.10
AC-4CABLE-25	4-pin accessory cable, 25 ft.	40.66
AC-4CABLE-50	4-pin accessory cable, 50 ft.	56.36
AC-4CABLE-100	4-pin accessory cable, 100 ft.	84.89

APOLLO CLIP LIGHT Provides a clean, simple solution for safer backstage work and crossover movement. Equipped with a gel retainer, mounting hardware, and a 9" diameter piece of AP4150 New York Blue Apollo Gel, the 8 1/2" Apollo Clip Light eliminates the awkward and unsightly process of taping gels to these handy lights. Sold in packs of 4.

ITEM	DESCRIPTION	PRICE
AC-CLIP-LIGHT	Clip Light, 4 pack	53.50



APOLLO GOBO TOOLKIT The purpose of the Gobo Toolkit is to train and educate. It introduces the basics of using gobos to create visual effects in general stage light applications. Kit contains (24) designed B-Round metal gobos, (1) Moon Natural B-Round B&W Glass Gobo, (1) Apollo SuperHolder™, (1) Creative Effects Guide, (1) instructional DVD and (1) resource CD.

ITEM	DESCRIPTION	PRICE
AC-GOBO-TOOLKIT	B-size Gobo kit, 24 metal gobos, 1 glass gobo, holder	226.96



AUDIO



COMPUTER AV



VIDEO



LIGHTS



MUSIC



ACCESSORIES



Follow us!

Let us show you exactly what to expect with our lighting design computer modeling & pre-visualization.